Single
Packs

Single Pack NLV8.0CN 100-240V 50/60Hz PM

Single pack code number: **195B4850**

Position	Title	Code	Amount
1	Compressor NLV8.0CN	105H7865	1
2	Electronic unit NLV	105N4911	1
3	Cover	103N2008	1
4	Bolt joint for one compressor | M6 | ø16mm	118-1917	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved.

型号

NLV8.0CN

采购代码:

105H7865

压缩机数据

制冷剂	**R290**
制冷剂最大充注量	**300g / 10.58oz**
重量	**10.80 kg / 23.81lbs**
排气量	**7.96 cm3 / 0.49cu.in**
每托盘压缩机数量	**80**



基本信息 NLV8.0CN 和控制器

–	Conf. 1	Conf. 2	Conf. 3	Conf. 4
单包装采购代码:	105N4866	105N4910	105N4960	105N4962
供电电源 (标称)	100-240 V,50/60 Hz	220-240 V,50/60 Hz	100-240 V,50/60 Hz	100-240 V,50/60 Hz
电机相数	1~AC	1~AC	1~AC	1~AC
认证	VDE, UL, CCC, CB	VDE, CCC	VDE, UL, CCC, CB	VDE, UL, CCC, CB
启动力矩	HST	HST	HST	HST
制冷剂	R290	R290	R290	R290
应用	L+MBP	L+MBP	L+MBP	L+MBP
热气除霜	OK	OK	OK	OK
长时间高负荷运行	OK	OK	OK	OK
保护器类型	Mechanic	Mechanic	Mechanic	Mechanic

应用说明

- 保护接地（PE）端子位于压缩机上的 PE 冲压标记处
- 带伸缩连接管的直吸结构

型号
NLV8.0CN

采购代码:
105H7865

设计信息


润滑油类型	**POE**	保护器类型	**内置**
润滑油黏度	**32cSt**	最高绕组温度	**125 °C**
润滑油注油量	**300 / 10.14fl.oz**	最高排气温度	**130°C / 266°F**
壳体内自由空间容积	**2,360 cm3 / 79.80fl.oz**		

尺寸信息

壳体


A 高度	**203mm / 7.99in**
B 高度	**197mm / 7.76in**
C 外壳长度	**205mm / 8.07in**
D 长度（含保护罩）	**252mm / 9.92in**
E 宽度	**166mm / 6.54in**

在此查找 3D 模型




连接管	吸气管 X	排气管 Y	工艺管 Z
直径 [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.11–6.29 / 0.24–0.25in	øi 6.11–6.29 / 0.24–0.25in
材料	CU	CU	CU
水平角度 ±2°	0°	0°	0°
垂直角度 ±2°	15°	21°	155°
位置 l/h/w [mm]	132/68.5/56.7 / 5.20/2.70/2.23in	94/101.7/81 / 3.70/4.00/3.19in	-109.3/94.3/72 / -4.30/3.71/2.83in
直管长度 [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

安装附件




单位：mm [in]

螺栓式



插片式



	单台包装	批量包装
螺栓式 | M6 | ø16mm	118-1917	118-1918
螺栓式 | ø1/4" | ø16mm	118-1946	–
螺栓式 | ø1/4" | ø19mm	118-1949	–
插片式 | ø7,3 | ø16mm	118-1947	118-1919


型号
NLV8.0CN


系统设计

采购代码:
105H7865

系统设计

运行范围 R290






系统冷却条件

压缩机和控制器冷却: 风冷 3m/s

需保证压缩机与控制器的冷却风速达到3m/s

需保证气流能直接冷却控制器的散热片



附件（压缩机+控制器）

103N2008	塑料保护罩	1 件

型号 采购代码:


NLV8.0CN 控制器概览 **105H7865**

控制器概览


–	**Conf. 1**	**Conf. 2**	**Conf. 3**	**Conf. 4**
单包装采购代码:	105N4866	105N4910	105N4960	105N4962
工业包装采购代码:	105N4867 (8)	105N4911 (8)	105N4961 (8)	105N4963 (8)
标称电压:	100-240 V,50/60 Hz	220-240 V,50/60 Hz	100-240 V,50/60 Hz	100-240 V,50/60 Hz
电压范围	90-150/180-270 V	180-270 V	90-150/180-270 V	90-150/180-270 V
最大输出功率	1000 W	1000 W	1000 W	1000 W
压缩机转速范围:	2000-4500 rpm	2000-4500 rpm	2000-4500 rpm	2000-4500 rpm
电缆长度:	680 mm	680 mm	680 mm	915 mm
防护等级:	IP43	IP54	IP54	IP54
堵转电流:	1,2 A	1,2 A	1,2 A	1,2 A
AEO and Defrost pin	–	Yes	Yes	Yes
Frequency input	–	Yes	Yes	Yes
Modbus input	RS485	SWI	SWI	SWI
控制器接线	» 控制器接线	» 控制器接线	» 控制器接线	» 控制器接线

控制器尺寸

Conf. 1



Conf. 2, 3, 4



操作说明

变频压缩机及控制器的正确安装与运行，请参阅操作说明书。本文件包含控制器的电气安装、转速控制以及技术参数相关内容。
» 下载操作说明书

型号

NLV8.0CN

采购代码:

105H7865

标准工况下性能参数 — 2000 rpm

R290, 240 V/50 Hz, 风冷 3m/s

pe	pc	RGT	Tliq	制冷量			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**260**	887	224	**1.77**	6.04	147	0.71	2.64	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**192**	654	165	**1.36**	4.64	141	0.69	2.40	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**140**	478	120	**1.42**	4.85	99	0.58	1.61	**EN12900 LBP**
-6.7 20	54.4 129.9	35 95	46.1 115	**482**	1644	414	**2.36**	8.04	204	0.91	5.52	**ASHRAE MBP**
-10 14	55 131	32 89.6	55 131	**382**	1303	328	**1.95**	6.67	196	0.88	4.86	**CECOMAF MBP**
-10 14	45 113	20 68	45 113	**421**	1435	362	**2.41**	8.22	175	0.81	5.18	**EN12900 MBP**

性能参数表 — 2000 rpm

R290, 240 V/50 Hz, 风冷 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-40	-40	**92**	315	79	**1.07**	3.65	86	0.56	1.04
-30	-22	**176**	599	151	**1.51**	5.14	117	0.62	1.99
-20	-4	**289**	986	249	**1.95**	6.66	148	0.72	3.29
-10	14	**437**	1492	376	**2.50**	8.54	175	0.81	5.02
0	32	**626**	2136	538	**3.27**	11.15	192	0.87	7.28
10	50	**860**	2935	740	**4.46**	15.20	193	0.87	10.17

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-40	-40	**68**	232	58	**0.77**	2.63	88	0.56	0.84
-30	-22	**144**	491	124	**1.18**	4.02	122	0.64	1.80
-20	-4	**247**	842	212	**1.54**	5.27	160	0.76	3.11
-10	14	**382**	1303	328	**1.95**	6.67	196	0.88	4.86
0	32	**554**	1892	477	**2.48**	8.45	224	0.99	7.15
10	50	**770**	2626	662	**3.21**	10.96	240	1.06	10.11

型号

NLV8.0CN

采购代码:

105H7865

标准工况下性能参数 — 4500 rpm

R290, 240 V/50 Hz, 风冷 3m/s

pe	pc	RGT	Tliq	制冷量			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**622**	2124	535	**1.83**	6.23	341	1.49	6.32	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**462**	1578	398	**1.41**	4.81	328	1.43	5.80	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**340**	1160	292	**1.48**	5.06	229	1.04	3.90	**EN12900 LBP**
-6.7 20	54.4 129.9	35 95	46.1 115	**1098**	3746	944	**2.34**	7.97	470	2.02	12.57	**ASHRAE MBP**
-10 14	55 131	32 89.6	55 131	**878**	2994	755	**1.95**	6.66	449	1.93	11.16	**CECOMAF MBP**
-10 14	45 113	20 68	45 113	**953**	3251	819	**2.38**	8.10	401	1.73	11.73	**EN12900 MBP**

性能参数表 — 4500 rpm

R290, 240 V/50 Hz, 风冷 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-40	-40	**230**	785	198	**1.14**	3.89	202	0.93	2.59
-30	-22	**423**	1443	364	**1.56**	5.32	271	1.21	4.78
-20	-4	**671**	2289	577	**1.97**	6.72	341	1.49	7.63
-10	14	**990**	3380	852	**2.47**	8.42	401	1.73	11.37
0	32	**1398**	4770	1202	**3.16**	10.79	442	1.90	16.25
10	50	**1909**	6515	1642	**4.20**	14.34	454	1.95	22.58

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-40	-40	**169**	575	145	**0.81**	2.76	208	0.96	2.10
-30	-22	**354**	1207	304	**1.24**	4.22	286	1.27	4.42
-20	-4	**585**	1995	503	**1.58**	5.39	370	1.60	7.36
-10	14	**878**	2994	755	**1.95**	6.66	449	1.93	11.16
0	32	**1249**	4261	1074	**2.43**	8.28	515	2.21	16.10
10	50	**1715**	5851	1475	**3.08**	10.52	556	2.38	22.53

型号
NLV8.0CN

采购代码:
105H7865


最佳性能


R290, 240 V/50 Hz, 风冷 3m/s
显示在每个标准工况下达到最高 COP 的转速 (RPM)。

pe	pc	RGT	Tliq	制冷量			COP	EER	P	RPM	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[rpm]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**410**	1400	353	**1.86**	6.36	220	**3000**	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**305**	1040	262	**1.44**	4.91	212	**3000**	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**224**	765	193	**1.51**	5.17	148	**3000**	**EN12900 LBP**
-6.7 20	54.4 129.9	35 95	46.1 115	**724**	2470	623	**2.39**	8.16	303	**3000**	**ASHRAE MBP**
-10 14	55 131	32 89.6	55 131	**579**	1974	498	**2.00**	6.82	290	**3000**	**CECOMAF MBP**
-10 14	45 113	20 68	45 113	**628**	2143	540	**2.43**	8.29	259	**3000**	**EN12900 MBP**

制冷量与 COP

R290, 240 V/50 Hz, 风冷 3m/s






Instructions


NLV/MN-UV Compressors
100-240 V, 50/60 Hz
105N4960/105N4964
Controllers


SECOP


Keep electrical equipment clear from oil, chemicals, and water











Instructions

NLV/MN-UV Compressors
100-240 V, 50/60 Hz
105N4960/105N4964
Controllers

SECOP


Keep electrical equipment clear from oil, chemicals, and water




Service/Repair – R170, R290, R1270

(applies to all flammable refrigerants)






Brazing on Suction Connectors (Direct Intake)



! max. 150°C/302°F ! at socket


brazing solder: phosphor (LP7) or silver

Refer to Product Bulletin: **Brazing on Suction Connectors (Compressors with Direct Suction Intake)**



Airflow	3 m/s
Operating conditions	+ 5 °C to 43 °C - humidity < 90 % rH non condensing
Storage conditions	-25 °C to 70 °C - humidity < 90 % rH non condensing
Supply voltage	100-240 V (± 10 %)
Frequency	50/60 Hz
Input power, max.	1000 W

Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**




Instructions


NLV/MN-UV Compressors
100-240 V, 50/60 Hz
105N4962/105N4966/
105N4972 Controllers


SECOP


Keep electrical equipment clear from oil, chemicals, and water











Instructions

NLV/MN-UV Compressors
100-240 V, 50/60 Hz
105N4962/105N4966/
105N4972 Controllers

SECOP


Keep electrical equipment clear from oil, chemicals, and water




Service/Repair – R170, R290, R1270

(applies to all flammable refrigerants)






Brazing on Suction Connectors (Direct Intake)



! max. 150°C/302°F ! at socket


brazing solder: phosphor (LP7) or silver

Refer to Product Bulletin: **Brazing on Suction Connectors (Compressors with Direct Suction Intake)**



Airflow	3 m/s
Operating conditions	+ 5 °C to 43 °C - humidity < 90 % rH non condensing
Storage conditions	-25 °C to 70 °C - humidity < 90 % rH non condensing
Supply voltage	100-240 V (± 10 %)
Frequency	50/60 Hz
Input power, max.	1000 W

Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**




Instructions


NLV/MN-UV Compressors
220-240 V, 50/60 Hz
105N491x Series
Controllers


SECOP


Keep electrical equipment clear from oil, chemicals, and water











Instructions

NLV/MN-UV Compressors
220-240 V, 50/60 Hz
105N491x Series
Controllers

SECOP


Keep electrical equipment clear from oil, chemicals, and water




Service/Repair – R170, R290, R1270

(applies to all flammable refrigerants)






Brazing on Suction Connectors (Direct Intake)



! max. 150°C/302°F ! at socket


brazing solder: phosphor (LP7) or silver

Refer to Product Bulletin: **Brazing on Suction Connectors (Compressors with Direct Suction Intake)**



Airflow	3 m/s
Operating conditions	+ 5 °C to 43 °C - humidity < 90 % rH non condensing
Storage conditions	-25 °C to 70 °C - humidity < 90 % rH non condensing
Supply voltage	220-240 V (± 10 %)
Frequency	50/60 Hz
Input power, max.	1000 W

Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**




Instructions

NLV Compressors
100-240 V, 50/60 Hz
105N486x Series
Controllers


SECOP


Keep electrical equipment clear from oil, chemicals, and water





Mains	red	**S1**	red
RL 1	blue	**S2**	blue
RL 2	yellow	**S3**	black
RL 3	black	**S4**	yellow
RL 4, 5	grey	**AIO**	brown
RL 6, 7	brown	**DIO1**	grey
RL 8	green	**DIO2**	pink
		Display	green





Instructions

NLV Compressors
100-240 V, 50/60 Hz
105N486x Series
Controllers

SECOP


Keep electrical equipment clear from oil, chemicals, and water




Service/Repair – R170, R290, R1270

(applies to all flammable refrigerants)






Brazing on Suction Connectors (Direct Intake)



! max. 150°C/302°F ! at socket

brazing solder: phosphor (LP7) or silver

Refer to Product Bulletin: **Brazing on Suction Connectors (Compressors with Direct Suction Intake)**



Airflow	3 m/s
Operating conditions	+ 5 °C to 43 °C - humidity < 90 % rH non condensing
Storage conditions	-25 °C to 70 °C - humidity < 90 % rH non condensing
Supply voltage	100-240 V (± 10 %)
Frequency	50/60 Hz
Input power, max.	1000 W

Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**