Single
Packs

Single Pack SC15MLX.2 208-230V 60Hz CSCR

Single pack code number: **195B4160**

Position	Title	Code	Amount
1	Compressor SC15MLX.2	104L2803	1
2	SC starting device	117-7058	1
3	Cord relief	103N1004	1
4	Cover	103N2008	1
5	Bolt joint for one compressor | M6 | ø16mm	118-1917	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved.

Model
SC15MLX.2

Sales code:
104L2803

Compressor Data

Refrigerant(s)	**R404A / R507**
Refr. charge - tech. limit	**1300g / 45.86oz**
Weight	**13.70 kg / 30.20lbs**
Displacement	**15.28 cm3 / 0.93cu.in**
Compressors on pallet	**80**

General – Configurations With SC15MLX.2

–	**Conf. 1**
Motor configuration	CSCR
Power supply (nominal)	208-230 V/60 Hz
Number of phases	1
Voltage range	187-254 V
Approvals	UL, KC
Starting torque	HST
Refrigerant	R404A
Application	MBP
Hot gas defrost	OK
Long interval pull down	OK

Application Notes

- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
SC15MLX.2

Sales code:
104L2803

Compressor Design

Oil type	**POE**	Winding resistance main	**2.6 Ohm**
Oil viscosity	**32cSt**	Winding resistance aux	**13 Ohm**
Oil quantity	**550 / 18.60fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**1,460 cm3 / 49.37fl.oz**	Max. discharge temp.	**130°C / 266°F**
Motor protection	**internal**		

Compressor Dimensions

Housing

A Height	**219mm / 8.62in**
B Height	**213mm / 8.39in**
C Length shell	**239mm / 9.41in**
D Length w. cover	**255mm / 10.04in**
E Width	**151mm / 5.94in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 9.54–9.72 / 0.38–0.38in	øi 6.41–6.59 / 0.25–0.26in	øi 6.41–6.59 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	37°	37°	143°
Vertical angle ±2°	30°	0°	150°
Position l/h/w [mm]	107/193/55 / 4.21/7.60/2.17in	115/110/63 / 4.53/4.33/2.48in	-107/193/55 / -4.21/7.60/2.17in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Bolt joint | ø1/4" | ø19mm	118-1949	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
SC15MLX.2 Configuration 1

Sales code:
104L2803

Configuration

Motor configuration	**CSCR**
Power supply (nominal)	**208-230 V/60 Hz 1~**
Refrigerant	**R404A**
Application	**MBP**
Voltage range	**187-254 V**
Starting torque	**HST**
Approvals	**UL, KC**
Starting device type	**relay**
Run capacitor	**15 µF**
Start capacitor	**125 µF**
LRA (locked rotor amps / 4s/ U(N))	**32 A**
RLA (rated load amps / 1s/ U(N))	**5 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components
a3 SC starter kit 117-7058
b plastic cover 103N2008
d cord relief 103N1004

Operation Pressure Range





Model

SC15MLX.2 Configuration 1

Sales code:

104L2803

Standard Conditions

R404A, 230 V/60 Hz, CSCR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-6.7 20	54.4 129.9	35 95	46.1 115	**1518**	5178	1305	**1.56**	5.31	975	4.35	41.69	**ASHRAE MBP**
-10 14	55 131	32 89.6	55 131	**1131**	3859	973	**1.22**	4.17	926	4.13	36.15	**CECOMAF MBP**
-10 14	45 113	20 68	45 113	**1337**	4561	1150	**1.55**	5.30	860	3.88	40.19	**EN12900 MBP**
-6.7 20	48.8 119.8	18.3 64.9	48.8 119.8	**1391**	4746	1196	**1.50**	5.10	930	4.19	45.33	**ARI540 MBP**
-10 14	45 113	32 89.6	45 113	**1418**	4838	1219	**1.65**	5.63	860	3.88	38.99	**opt MBP 1**
-25 -13	45 113	32 89.6	45 113	**722**	2465	621	**1.11**	3.77	653	3.00	19.45	**opt MBP 2**

Performance Tables

R404A, 230 V/60 Hz, CSCR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-23.3	-10	**784**	2674	674	**1.16**	3.95	676	3.09	21.14
-20	-4	**915**	3121	787	**1.27**	4.33	722	3.27	24.77
-15	5	**1145**	3907	985	**1.45**	4.94	790	3.56	31.23
-10	14	**1418**	4838	1219	**1.65**	5.63	860	3.88	38.99
-5	23	**1737**	5927	1494	**1.87**	6.37	931	4.21	48.23
0	32	**2107**	7188	1812	**2.10**	7.16	1004	4.55	59.16
5	41	**2531**	8635	2176	**2.34**	8.00	1080	4.92	72.03
7.2	45	**2735**	9333	2352	**2.46**	8.38	1114	5.09	78.38

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-23.3	-10	**623**	2125	536	**0.88**	3.01	705	3.23	19.47
-20	-4	**726**	2478	625	**0.96**	3.26	760	3.44	22.80
-15	5	**910**	3106	783	**1.08**	3.68	842	3.77	28.82
-10	14	**1131**	3859	973	**1.22**	4.17	926	4.13	36.15
-5	23	**1392**	4750	1197	**1.38**	4.71	1009	4.50	45.01
0	32	**1698**	5794	1460	**1.55**	5.30	1094	4.90	55.63
5	41	**2053**	7004	1765	**1.74**	5.93	1181	5.31	68.32
7.2	45	**2225**	7593	1914	**1.82**	6.22	1220	5.50	74.65



SC Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

RSIR





CSIR





CSCR







SC Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



CSCR



Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**