Single
Packs

Single Pack NLE10CN 115V 60Hz CSIR

Single pack code number: **195B4308**

Position	Title	Code	Amount
1	Compressor NLE10CN	105H6195	1
2	Bolt joint for one compressor | M6 | ø16mm	118-1917	1
Below electrical equipment is pre-assembled on the compressor:			
3	Starting relay	117U7018	1
4	Starting capacitor (280µF 125V, 6.3mm)	117U5025	1
5	Cable clamp	103N0489	1
6	Yoke	103N0126	1
7	Cover	103N2011	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved.

Model
NLE10CN

Sales code:
105H6195

Compressor Data

Refrigerant(s)	**R290**
Refr. charge - tech. limit	**400g / 14.11oz**
Weight	**10.90 kg / 24.03lbs**
Displacement	**10.09 cm3 / 0.62cu.in**
Compressors on pallet	**80**

General – Configurations With NLE10CN

–	**Conf. 1**
Motor configuration	CSIR
Power supply (nominal)	115 V/60 Hz
Number of phases	1
Voltage range	103-127 V
Approvals	UL
Starting torque	HST
Refrigerant	R290
Application	LBP+MBP
Hot gas defrost	OK
Long interval pull down	OK

Application Notes

- Electrical equipment is included and pre-assembled to compressor.
- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
NLE10CN

Sales code:
105H6195

Compressor Design

Oil type	**32 cSt POE RL32DR**	Winding resistance main	**1.56 Ohm**
Oil viscosity	**32cSt**	Winding resistance aux	**4.4 Ohm**
Oil quantity	**268 / 9.06fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**2,360 cm3 / 79.80fl.oz**	Max. discharge temp.	**120°C / 248°F**
Motor protection	**internal**		

Compressor Dimensions

Housing

A Height	**203mm / 7.99in**
B Height	**197mm / 7.76in**
C Length shell	**205mm / 8.07in**
D Length w. cover	**254mm / 10.00in**
E Width	**166mm / 6.54in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.41–6.59 / 0.25–0.26in	øi 6.41–6.59 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	0°	0°	0°
Vertical angle ±2°	15°	21°	155°
Position l/h/w [mm]	132/68.5/56.7 / 5.20/2.70/2.23in	94/101.7/81 / 3.70/4.00/3.19in	-109.3/94.3/72 / -4.30/3.71/2.83in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Bolt joint | ø1/4" | ø19mm	118-1949	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
NLE10CN Configuration 1

Sales code:
105H6195

Configuration

Motor configuration	**CSIR**
Power supply (nominal)	**115 V/60 Hz 1~**
Refrigerant	**R290**
Application	**LBP+MBP**
Voltage range	**103-127 V**
Starting torque	**HST**
Approvals	**UL**
Starting device type	**relay**
Run capacitor	**-/-**
Start capacitor	**280 µF**
LRA (locked rotor amps / 4s/ U(N))	**34.53 A**
RLA (rated load amps / 1s/ U(N))	**5.6 A**
Cut in current (U(N))	**34.53 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components (already pre-assembled)
a2 current relay 117U7018
c start capacitor (280µF) 117U5025
b plastic cover 103N2011
d cord relief 103N1010

Operation Pressure Range





Model
NLE10CN Configuration 1

Sales code:
105H6195

Standard Conditions

R290, 115 V/60 Hz, CSIR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**610**	2082	525	**1.53**	5.22	399	5.18	6.20	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**456**	1557	393	**1.17**	4.00	390	5.13	5.72	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**362**	1234	311	**1.26**	4.31	286	4.53	4.15	**EN12900 LBP**
-6.7 20	54.4 129.9	35 95	46.1 115	**1069**	3648	919	**2.05**	6.99	522	5.95	12.24	**ASHRAE MBP**
-10 14	55 131	32 89.6	55 131	**854**	2914	735	**1.70**	5.80	503	5.84	10.86	**CECOMAF MBP**
-10 14	45 113	20 68	45 113	**935**	3192	804	**2.04**	6.96	459	5.48	11.51	**EN12900 MBP**

Performance Tables

R290, 115 V/60 Hz, CSIR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-35	-31	**339**	1157	292	**1.18**	4.01	288	4.51	3.82
-30	-22	**429**	1462	369	**1.31**	4.49	326	4.74	4.84
-20	-4	**662**	2259	569	**1.68**	5.74	394	5.12	7.53
-10	14	**972**	3318	836	**2.12**	7.23	459	5.48	11.17
0	32	**1364**	4656	1173	**2.58**	8.81	529	5.87	15.87
7.2	45	**1700**	5800	1462	**2.90**	9.89	586	6.20	20.00

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-35	-31	**282**	961	242	**0.93**	3.16	304	4.62	3.51
-30	-22	**360**	1230	310	**1.03**	3.52	349	4.88	4.50
-20	-4	**570**	1946	490	**1.33**	4.54	428	5.37	7.18
-10	14	**854**	2914	735	**1.70**	5.80	503	5.84	10.86
0	32	**1216**	4151	1046	**2.10**	7.16	580	6.36	15.69
7.2	45	**1529**	5216	1315	**2.39**	8.14	640	6.80	19.97



NL Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

RSIR





CSIR





RSCR







NL Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



Brazing on Suction Connectors (Direct Intake)

representative image



! max. 150°C/302°F ! at socket

brazing solder: phosphor (LP7) or silver

Refer to Product Bulletin:
Brazing on Suction Connectors (Compressors with Direct Suction Intake)

Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**