

Model
GS26GHX

Sales code:
107B0702

Compressor Data

Refrigerant(s)	R134a / R513A
Refr. charge - tech. limit	2000g / 70.55oz
Weight	19.10 kg / 42.11lbs
Displacement	26.30 cm3 / 1.60cu.in
Compressors on pallet	48



General – Configurations With GS26GHX

-	Conf. 1	Conf. 2
Motor configuration	CSCR	CSCR
Power supply (nominal)	220-240 V/50 Hz	220-240 V/50 Hz
Number of phases	1	1
Voltage range	198-254 V	198-254 V
Approvals	VDE	VDE
Starting torque	HST	HST
Refrigerant	R134a	R513A
Application	MBP+HBP	MBP+HBP
Hot gas defrost	OK	OK
Long interval pull down	OK	OK

Application Notes

- Cover, clamp, gasket: pre-assembled to compressor.
- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
GS26GHX

Sales code:
107B0702

Compressor Design


Oil type	POE	Free gas volume comp.	3,350 cm ³ / 113.28fl.oz
Oil viscosity	32,5cSt	Motor protection	internal
Oil quantity	902 / 30.50fl.oz	Max. discharge temp.	130°C / 266°F

Compressor Dimensions

Housing


A Height	259mm / 10.20in
B Height	247mm / 9.72in
C Length shell	224mm / 8.82in
D Length w. cover	232mm / 9.13in
E Width	173mm / 6.81in

[Find 3D Model here](#)




Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 12.75–13.05 / 0.50–0.51in	øi 8.15–8.25 / 0.32–0.32in	øi 6.4–6.6 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	0°	0°	0°
Vertical angle ±2°	90°	71°	90°
Position l/h/w [mm]	-94.5/234/-84 / -3.72/9.21/-3.31in	-105/84/-84 / -4.13/3.31/-3.31in	94.5/234/84 / 3.72/9.21/3.31in
Straight tube l. [mm]	18 / 0.71in	22.5 / 0.89in	15 / 0.59in

Mounting Accessories



Bolt joint



Dimensions in mm [in]

	one comp.	multi pack
Bolt joint M8 ø19mm	107B9150	-

Model

GS26GHX

Configuration 1

Sales code:

107B0702

Configuration

Motor configuration	CSCR
Power supply (nominal)	220-240 V/50 Hz 1~
Refrigerant	R134a
Application	MBP+HBP
Voltage range	198-254 V
Starting torque	HST
Approvals	VDE
Starting device type	relay
Run capacitor	20 µF
Start capacitor	80 µF
LRA (locked rotor amps / 4s/ U(N))	40 A
RLA (rated load amps / 1s/ U(N))	5.6 A
Cut in current (U(N))	40 A

Ambient/ machine room temperatures minimum /maximum


Ambient temperature range: 10 - 43°C / 50 - 109°F

Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling

fan 3m/s

Electrical Accessories / Wiring Diagram

[View full size](#)

Components (cover, clamp, gasket: pre assembled)



a3 GS starter kit (600mm) 117-7070

b cover 107B9101

b2 gasket 107B9100

b1 clamp 107B9104

Operation Pressure Range



Model
GS26GHX

Configuration 1

Sales code:
107B0702

Standard Conditions

R134a, 220 V/50 Hz, CSCR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	m	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
7.2 45	54.4 129.9	35 95	46.1 115	2608	8897	2243	2.49	8.51	1045	4.91	57.72	ASHRAE HBP
5 41	55 131	32 89.6	55 131	2152	7342	1851	2.13	7.26	1011	4.75	52.85	CECOMAF HBP
5 41	50 122	20 68	50 122	2239	7638	1925	2.31	7.88	970	4.56	56.15	EN12900 HBP
-6.7 20	54.4 129.9	35 95	46.1 115	1443	4924	1241	1.79	6.09	808	3.83	31.42	ASHRAE MBP
-10 14	55 131	32 89.6	55 131	1119	3819	963	1.48	5.05	756	3.62	26.98	CECOMAF MBP
-10 14	45 113	20 68	45 113	1275	4352	1097	1.78	6.07	717	3.42	29.74	EN12900 MBP

Performance Tables

R134a, 220 V/50 Hz, CSCR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	m
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-15	5	1040	3548	894	1.60	5.46	650	3.15	22.62
-10	14	1321	4507	1136	1.84	6.29	717	3.42	28.85
-5	23	1657	5653	1425	2.11	7.21	785	3.72	36.36
0	32	2056	7013	1768	2.40	8.20	855	4.04	45.35
5	41	2524	8613	2171	2.71	9.26	930	4.38	56.07
10	50	3072	10480	2641	3.04	10.37	1010	4.75	68.75
15	59	3704	12639	3186	3.38	11.52	1097	5.14	83.69

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-15	5	877	2994	755	1.30	4.44	675	3.29	21.06
-10	14	1119	3819	963	1.48	5.05	756	3.62	26.98
-5	23	1407	4801	1210	1.68	5.72	839	3.97	34.10
0	32	1749	5966	1504	1.89	6.46	923	4.35	42.64
5	41	2152	7342	1851	2.13	7.26	1011	4.75	52.85
10	50	2624	8953	2257	2.38	8.12	1103	5.17	65.01
15	59	3174	10828	2729	2.64	9.01	1202	5.62	79.43

Model
GS26GHX

Configuration 2

Sales code:
107B0702

Configuration

Motor configuration	CSCR
Power supply (nominal)	220-240 V/50 Hz 1~
Refrigerant	R513A
Application	MBP+HBP
Voltage range	198-254 V
Starting torque	HST
Approvals	VDE
Starting device type	relay
Run capacitor	20 µF
Start capacitor	80 µF
LRA (locked rotor amps / 4s/ U(N))	40 A
RLA (rated load amps / 1s/ U(N))	5.6 A
Cut in current (U(N))	40 A

Ambient/ machine room temperatures minimum /maximum


Ambient temperature range: 10 - 43°C / 50 - 109°F

Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling

fan 3m/s

Electrical Accessories / Wiring Diagram



[View full size](#)

Components (cover, clamp, gasket: pre assembled)



a3 GS starter kit (600mm) 117-7070

b cover 107B9101

b2 gasket 107B9100

b1 clamp 107B9104

Operation Pressure Range



Model
GS26GHX

Configuration 2

Sales code:
107B0702

Standard Conditions

R513A, 220 V/50 Hz, CSCR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	m	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
7.2 45	54.4 129.9	35 95	46.1 115	2682	9152	2307	2.48	8.44	1084	5.96	68.16	ASHRAE HBP
5 41	55 131	32 89.6	55 131	2180	7440	1875	2.08	7.09	1049	5.82	62.53	CECOMAF HBP
5 41	50 122	20 68	50 122	2255	7694	1939	2.24	7.65	1006	5.63	66.49	EN12900 HBP
-6.7 20	54.4 129.9	35 95	46.1 115	1514	5165	1302	1.79	6.09	848	4.93	37.74	ASHRAE MBP
-10 14	55 131	32 89.6	55 131	1161	3961	998	1.46	4.97	797	4.70	32.57	CECOMAF MBP
-10 14	45 113	20 68	45 113	1326	4525	1141	1.75	5.99	756	4.51	35.91	EN12900 MBP

Performance Tables

R513A, 220 V/50 Hz, CSCR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	m
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-15	5	1106	3772	951	1.60	5.47	690	4.18	27.55
-10	14	1392	4748	1197	1.84	6.28	756	4.51	34.84
-5	23	1731	5908	1489	2.11	7.19	822	4.82	43.58
0	32	2132	7275	1834	2.39	8.17	891	5.13	54.02
5	41	2602	8877	2237	2.70	9.21	964	5.45	66.41
10	50	3147	10738	2706	3.01	10.27	1045	5.80	81.05
15	59	3776	12882	3247	3.32	11.34	1136	6.18	98.29

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-15	5	919	3136	791	1.28	4.38	715	4.31	25.66
-10	14	1161	3961	998	1.46	4.97	797	4.70	32.57
-5	23	1447	4936	1244	1.65	5.62	878	5.07	40.84
0	32	1784	6088	1534	1.85	6.33	962	5.44	50.73
5	41	2180	7440	1875	2.08	7.09	1049	5.82	62.53
10	50	2643	9018	2273	2.31	7.89	1143	6.21	76.57
15	59	3179	10847	2734	2.55	8.71	1246	6.63	93.22