

Model
HMK80AA

Sales code:
16050800

Compressor Data

Refrigerant(s)	R600a
Refr. charge - tech. limit	150g / 5.29oz
Weight	7.60 kg / 16.76lbs
Displacement	8.10 cm3 / 0.49cu.in
Compressors on pallet	100



General – Configurations With HMK80AA

-	Conf. 1	Conf. 2
Motor configuration	RSIR	RSIR
Power supply (nominal)	220-240 V/50 Hz	220-240 V/50 Hz
Number of phases	1	1
Voltage range	187-264 V	187-264 V
Approvals	VDE	VDE
Starting torque	LST	LST
Refrigerant	R600a	R600a
Application	LBP	LBP

Application Notes

- Various options of connectors are possible - please contact SECOP-Sales.
- Provision for PE Grounding is located at the PE Stamp on the compressor
- Housing with dip-tray fixture (omega bracket).
- Various options of connectors are possible - please contact SECOP-Sales.

Model
HMK80AA

Sales code:
16050800

Compressor Design


Oil type	Mineral	Motor protection	external
Oil viscosity	5cSt	Max. winding temp.	130 °C
Oil quantity	163 / 5.51fl.oz	Max. discharge temp.	120°C / 248°F
Free gas volume comp.	1,520 cm ³ / 51.40fl.oz		

Compressor Dimensions

Housing


A Height	174mm / 6.85in
B Height	167mm / 6.57in
C Length shell	194mm / 7.64in
D Length w. cover	238mm / 9.37in
E Width	151mm / 5.94in

[Find 3D Model here](#)




Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 6.16–6.24 / 0.24–0.25in	øi #N/A–#N/A	øi 6.11–6.29 / 0.24–0.25in
Material	CU	#N/A	CU
Horizontal angle ±2°	54°	35°	45°
Vertical angle ±2°	35°	40°	35°
Position l/h/w [mm]	120/92/56.7 / 4.72/3.62/2.23in	112/105.5/81 / 4.41/4.15/3.19in	-86/94.3/72 / -3.39/3.71/2.83in
Straight tube l. [mm]	13.5 / 0.53in	#N/A	13.5 / 0.53in

Mounting Accessories




Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
'4ZN' with rubber grommet	–	772N
'4ZN' with rubber grommet and sleeve for M6	–	768N
Bolt joint kit	–	4ZN + 118-1917 (18)
'4ZN' with Snap on kit	–	776N

Model
HMK80AA

Configuration 1

Sales code:
16050800

Configuration

Motor configuration	RSIR
Power supply (nominal)	220-240 V/50 Hz 1~
Refrigerant	R600a
Application	LBP
Voltage range	187-264 V
Starting torque	LST
Approvals	VDE
Starting device type	PTC
Run capacitor	-/-
Start capacitor	-/-
LRA (locked rotor amps / 4s/ U(N))	3.55 A
RLA (rated load amps / 1s/ U(N))	0.8 A
Cut in current (U(N))	10 A

Ambient/ machine room temperatures minimum /maximum


Ambient temperature range: 10 - 43°C / 50 - 109°F

Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling

static

Electrical Accessories / Wiring Diagram





[View full size](#)

Components

- . terminal board (PTC, 4.8mm) 15163500
- . Term. Board Cover 15759500
- . cable clamp 16058100
- . screw uni en iso 4757 10641201

Operation Pressure Range



Model
HMK80AA

Configuration 1

Sales code:
16050800

Standard Conditions

R600a, 220 V/50 Hz, RSIR, static

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	m	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	136	464	117	1.50	5.12	90	0.62	1.46	ASHRAE LBP
-25 -13	55 131	32 89.6	55 131	102	347	87	1.18	4.01	86	0.60	1.33	CECOMAF LBP
-35 -31	40 104	20 68	40 104	73	248	62	1.12	3.84	65	0.52	0.88	EN12900 LBP
-23.3 -10	48.8 119.8	4.4 39.9	48.8 119.8	110	376	95	1.25	4.25	89	0.61	1.61	ARI540 LBP
-23.3 -10	40.6 105.1	32.2 90	32.2 90	144	492	124	1.68	5.74	86	0.60	1.55	AHAM LBP
-25 -13	45 113	32 89.6	45 113	117	400	101	1.40	4.76	84	0.59	1.39	opt LBP

Performance Tables

R600a, 220 V/50 Hz, RSIR, static

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	m
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-35	-31	68	232	59	1.07	3.64	64	0.51	0.81
-30	-22	90	306	77	1.21	4.14	74	0.55	1.06
-25	-13	117	400	101	1.40	4.76	84	0.59	1.39
-20	-4	151	514	130	1.60	5.47	94	0.64	1.80
-15	5	190	649	164	1.83	6.23	104	0.69	2.27
-10	14	236	805	203	2.06	7.04	114	0.73	2.82
-5	23	287	980	247	2.31	7.87	125	0.79	3.45

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-35	-31	55	187	47	0.88	3.01	62	0.49	0.71
-30	-22	76	258	65	1.02	3.48	74	0.55	0.98
-25	-13	102	347	87	1.18	4.01	86	0.60	1.33
-20	-4	133	453	114	1.34	4.58	99	0.66	1.74
-15	5	169	578	146	1.51	5.16	112	0.72	2.22
-10	14	211	720	181	1.68	5.75	125	0.79	2.77
-5	23	258	879	222	1.86	6.33	139	0.85	3.39

Model
HMK80AA

Configuration 2

Sales code:
16050800

Configuration

Motor configuration	RSIR
Power supply (nominal)	220-240 V/50 Hz 1~
Refrigerant	R600a
Application	LBP
Voltage range	187-264 V
Starting torque	LST
Approvals	VDE
Starting device type	PTC
Run capacitor	-/-
Start capacitor	-/-
LRA (locked rotor amps / 4s/ U(N))	3.55 A
RLA (rated load amps / 1s/ U(N))	0.8 A
Cut in current (U(N))	10 A

Ambient/ machine room temperatures minimum /maximum


Ambient temperature range: 10 - 43°C / 50 - 109°F

Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling

static

Electrical Accessories / Wiring Diagram





[View full size](#)

Components

- . terminal board (PTC, 6.3mm) 15279300
- b** cover terminal board 10636401
- . cable clamp 16058100
- . screw - uni6954 10636000
- . screw - uni6954 10636200
- . screw uni en iso 4757 10641201

Operation Pressure Range



Model
HMK80AA

Configuration 2

Sales code:
16050800

Standard Conditions

R600a, 220 V/50 Hz, RSIR, static

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	m	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	136	464	117	1.50	5.12	90	0.62	1.46	ASHRAE LBP
-25 -13	55 131	32 89.6	55 131	102	347	87	1.18	4.01	86	0.60	1.33	CECOMAF LBP
-35 -31	40 104	20 68	40 104	73	248	62	1.12	3.84	65	0.52	0.88	EN12900 LBP
-23.3 -10	48.8 119.8	4.4 39.9	48.8 119.8	110	376	95	1.25	4.25	89	0.61	1.61	ARI540 LBP
-23.3 -10	40.6 105.1	32.2 90	32.2 90	144	492	124	1.68	5.74	86	0.60	1.55	AHAM LBP
-25 -13	45 113	32 89.6	45 113	117	400	101	1.40	4.76	84	0.59	1.39	opt LBP

Performance Tables

R600a, 220 V/50 Hz, RSIR, static

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	m
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-35	-31	68	232	59	1.07	3.64	64	0.51	0.81
-30	-22	90	306	77	1.21	4.14	74	0.55	1.06
-25	-13	117	400	101	1.40	4.76	84	0.59	1.39
-20	-4	151	514	130	1.60	5.47	94	0.64	1.80
-15	5	190	649	164	1.83	6.23	104	0.69	2.27
-10	14	236	805	203	2.06	7.04	114	0.73	2.82
-5	23	287	980	247	2.31	7.87	125	0.79	3.45

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-35	-31	55	187	47	0.88	3.01	62	0.49	0.71
-30	-22	76	258	65	1.02	3.48	74	0.55	0.98
-25	-13	102	347	87	1.18	4.01	86	0.60	1.33
-20	-4	133	453	114	1.34	4.58	99	0.66	1.74
-15	5	169	578	146	1.51	5.16	112	0.72	2.22
-10	14	211	720	181	1.68	5.75	125	0.79	2.77
-5	23	258	879	222	1.86	6.33	139	0.85	3.39