

HXK55AA KAPPA LBP Compressor Superior Efficiency R600a 220-240V 50Hz

General

Code number	CDO00045
Approvals	EN 60335-2-34 w. Annex AA
Compressors on pallet	100

Application

Application	LBP		
Frequency	Hz	50	60
Evaporating temperature	°C	-35 to -5	—
Voltage range	V	187 to 264	—
Max. condensing temperature continuous (short)	°C	60 (70)	—
Max. winding temperature continuous (short)	°C	130 (130)	—

Cooling requirements

Frequency	Hz	50			60		
Application		LBP	MBP	HBP	LBP	MBP	HBP
32°C		S	—	—	—	—	—
38°C		S	—	—	—	—	—
43°C		S	—	—	—	—	—
Remarks on application:							

Motor


Motor type	RSCR		
LRA (rated after 4 sec. UL984), HST LST	A	—	1.75
Cut in Current, HST LST	A	—	6.7
Resistance, main start winding (25°C)	Ω	35.9	23.6

Design




Displacement	cm ³	5.6
Oil quantity (type)	cm ³	165 (mineral)
Maximum refrigerant charge	g	150
Free gas volume in compressor	cm ³	1500
Weight without electrical equipment	kg	8.5

Dimensions

Height		mm	A	159
			B	165,5
Suction connector	location/I.D. mm angle		C	6.15 35°
	material comment		Copper Rubber plug	
Process connector	location/O.D. mm angle		D	6.00 35°
	material comment		Copper Rubber plug	
Discharge connector	location/I.D. mm angle		E	5.15 40°
	material comment		Copper Rubber plug	
Oil cooler connector	location/I.D. mm angle		F	–
	material comment		–	
Connector tolerance	I.D. mm		±0.05	
Remarks:				





- S = Static cooling normally sufficient
- O = Oil cooling
- F₁ = Fan cooling 1.5 m/s (compressor compartment temperature equal to ambient temperature)
- F₂ = Fan cooling 3.0 m/s necessary
- SG = Suction gas cooling normally sufficient
- = not applicable in this area



EN 12900 Household		220V, 50Hz, RC 2µF, ePTC consumption incl., static cooling (alternative use of PTC +2W)															
Evap. temp. in °C	-45	-40	-35	-30	-25	-23.3	-20	-15	-10	-6.7	-5	0	5	7.2	10	15	20
Capacity in W			35.9	52.3	72.0	79.5	95.1	121	151	172	184						
Power cons. in W			33.9	42.0	50.3	53.2	58.8	67.5	76.3	82.2	85.2						
Current cons. in A			0.19	0.21	0.24	0.25	0.27	0.30	0.33	0.35	0.36						
COP in W/W			1.06	1.24	1.43	1.49	1.62	1.80	1.98	2.10	2.16						

ASHRAE LBP		220V, 50Hz, RC 2µF, ePTC consumption incl., static cooling (alternative use of PTC +2W)															
Evap. temp. in °C	-45	-40	-35	-30	-25	-23.3	-20	-15	-10	-6.7	-5	0	5	7.2	10	15	20
Capacity in W			43.9	64.0	88.1	97.2	116	148	184	210	224						
Power cons. in W			34.0	42.0	50.2	53.0	58.6	67.1	75.7	81.5	84.5						
Current cons. in A			0.19	0.21	0.24	0.25	0.27	0.30	0.33	0.35	0.36						
COP in W/W			1.29	1.52	1.75	1.83	1.98	2.21	2.43	2.58	2.65						



Accessories for HXK55AA		Code number	Test conditions	EN 12900 Household	ASHRAE LBP
Run capacitor (compulsory) 4.8 mm or 6.3 mm spade connectors		2 µF	Condensing temperature	55°C	54.4°C
Terminal board 4.8 mm spade connectors (incl. ePTC and external protector)		ZX F6	Ambient temperature	32°C	32.2°C
Terminal board 6.3 mm spade connectors (incl. PTC and external protector)		DA F6	Suction gas temperature	32°C	32.2°C
Motor Protector AE 25 FJ x		ZA F6	Liquid temperature	no subcooling	32.2°C
		F6			
Evaporation tray (optional)		16299100			
All-in-one equipment, e.g. 4ZN		Code number	Mounting accessories		Code number
Cover / cable clamp + screws / earthing screw		16168000	on request, various options available		

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequent changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved. www.secop.com