

Model
KLE7.7CFHX

Sales code:
106G6813

Compressor Data

Refrigerant(s)	R134a / R513A
Refr. charge - tech. limit	300g / 10.58oz
Weight	9.60 kg / 21.16lbs
Displacement	7.70 cm3 / 0.47cu.in
Compressors on pallet	100



General – Configurations With KLE7.7CFHX

-	Conf. 1
Motor configuration	CSIR
Power supply (nominal)	115-127 V/60 Hz
Number of phases	1
Voltage range	95-140 V
Approvals	UL
Starting torque	HST
Refrigerant	R134a
Application	LBP+MBP
Hot gas defrost	OK
Long interval pull down	OK

Application Notes

- Electrical equipment is included and pre-assembled to compressor.
- Provision for PE Grounding is located at the PE Stamp on the compressor
- Suctiongas connector and Process connector can be switched (minor loss of cooling capacity)
- Good robustness against liquid intake.
- Ice-cube maker optimization - indirect suction intake.

Model
KLE7.7CFHX

Sales code:
106G6813

Compressor Design


Oil type	POE	Winding resistance main	2 Ohm
Oil viscosity	19,2cSt	Winding resistance aux	5.3 Ohm
Oil quantity	200 / 6.76fl.oz	Max. winding temp.	125 °C
Free gas volume comp.	1,575 cm3 / 53.26fl.oz	Max. discharge temp.	130°C / 266°F
Motor protection	external		

Compressor Dimensions

Housing


A Height	182mm / 7.17in
B Height	175mm / 6.89in
C Length shell	198mm / 7.80in
D Length w. cover	238mm / 9.37in
E Width	160mm / 6.30in

[Find 3D Model here](#)




Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.41–6.59 / 0.25–0.26in	øi 6.41–6.59 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	35°	13°	0°
Vertical angle ±2°	30°	40°	145°
Position l/h/w [mm]	119/73/59 / 4.69/2.87/2.32in	117/107/66 / 4.61/4.21/2.60in	-88/101/71 / -3.46/3.98/2.80in
Straight tube l. [mm]	13.5 / 0.53in	13.5 / 0.53in	13.5 / 0.53in


Mounting Accessories



Bolt joint



Snap-on



Dimensions in mm [in]

	one comp.	multi pack
Bolt joint M6 ø16mm	118-1917	118-1918
Bolt joint ø1/4" ø16mm	118-1946	-
Bolt joint ø1/4" ø19mm	118-1949	-
Snap-on ø7,3 ø16mm	118-1947	118-1919

Model

KLE7.7CFHX

Configuration 1

Sales code:

106G6813

Configuration

Motor configuration	CSIR
Power supply (nominal)	115-127 V/60 Hz 1~
Refrigerant	R134a
Application	LBP+MBP
Voltage range	95-140 V
Starting torque	HST
Approvals	UL
Starting device type	relay
Run capacitor	-/-
Start capacitor	240 µF
LRA (locked rotor amps / 4s/ U(N))	31.1 A
RLA (rated load amps / 1s/ U(N))	4.3 A
Cut in current (U(N))	31.5 A

Ambient/ machine room temperatures minimum /maximum


Ambient temperature range: 10 - 43°C / 50 - 109°F

Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling

fan 3m/s

Electrical Accessories / Wiring Diagram



[View full size](#)

Components (already pre-assembled)

a5 current relay (T1217/L6-S5) 117U7075

c start capacitor (240µF) 117U5002



b, d cover + clamp + screws (5VA-compl.) 103N0600

Alternative components

b, d 100x cover + clamp + screws (5VA) 103N2060

b, d cover + clamp + screws (5VA) in bag 103N1060

Operation Pressure Range



Model
KLE7.7CFHX

Configuration 1

Sales code:
106G6813

Standard Conditions

R134a, 120 V/60 Hz, CSIR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	m	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	266	909	229	1.33	4.55	200	2.74	5.17	ASHRAE LBP
-25 -13	55 131	32 89.6	55 131	196	668	168	1.02	3.48	192	2.69	4.67	CECOMAF LBP
-35 -31	40 104	20 68	40 104	133	455	115	0.97	3.32	137	2.38	2.92	EN12900 LBP
-6.7 20	54.4 129.9	35 95	46.1 115	542	1849	466	1.81	6.18	299	3.46	11.80	ASHRAE MBP
-10 14	55 131	32 89.6	55 131	423	1442	363	1.51	5.16	280	3.31	10.19	CECOMAF MBP
-10 14	45 113	20 68	45 113	468	1596	402	1.78	6.08	262	3.18	10.91	EN12900 MBP

Performance Tables

R134a, 120 V/60 Hz, CSIR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	m
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-32	-26	153	521	131	1.04	3.54	147	2.41	3.29
-30	-22	172	585	147	1.09	3.73	157	2.46	3.70
-20	-4	297	1014	256	1.43	4.88	208	2.79	6.44
-10	14	484	1653	417	1.85	6.30	262	3.18	10.58
0	32	745	2542	641	2.33	7.93	320	3.64	16.43
10	50	1090	3719	937	2.85	9.72	383	4.16	24.40

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-32	-26	127	435	110	0.82	2.80	155	2.48	3.03
-30	-22	145	494	125	0.88	2.99	166	2.54	3.45
-20	-4	258	880	222	1.17	4.00	220	2.87	6.17
-10	14	423	1442	363	1.51	5.16	280	3.31	10.19
0	32	650	2219	559	1.88	6.42	345	3.84	15.86
10	50	953	3251	819	2.28	7.79	418	4.45	23.61