

Model

SC15G

Sales code:

104G7555

Compressor Data

Refrigerant(s)	R134a
Refr. charge - tech. limit	1300g / 45.86oz
Weight	13.20 kg / 29.10lbs
Displacement	15.28 cm3 / 0.93cu.in
Compressors on pallet	80



General – Configurations With SC15G

-	Conf. 1
Motor configuration	CSIR
Power supply (nominal)	115 V/60 Hz
Number of phases	1
Voltage range	103-127 V
Approvals	UL
Starting torque	HST
Refrigerant	R134a
Application	LBP+MBP+HBP
Hot gas defrost	OK
Long interval pull down	OK

Application Notes

- Electrical equipment is included and pre-assembled to compressor.
- Provision for PE Grounding is located at the PE Stamp on the compressor

Model

Sales code:

SC15G

104G7555

Compressor Design


Oil type	POE	Winding resistance main	1.000 Ohm
Oil viscosity	22cSt	Winding resistance aux	4.30 Ohm
Oil quantity	554 / 18.73fl.oz	Max. winding temp.	125 °C
Free gas volume comp.	1,460 cm3 / 49.37fl.oz	Max. discharge temp.	130°C / 266°F
Motor protection	internal		

Compressor Dimensions

Housing


A Height	209mm / 8.23in
B Height	203mm / 7.99in
C Length shell	218mm / 8.58in
D Length w. cover	255mm / 10.04in
E Width	151mm / 5.94in

[Find 3D Model here](#)




Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.41–6.59 / 0.25–0.26in	øi 6.41–6.59 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	37°	37°	143°
Vertical angle ±2°	30°	0°	150°
Position l/h/w [mm]	107/183/55 / 4.21/7.20/2.17in	115/100/63 / 4.53/3.94/2.48in	-107/183/55 / -4.21/7.20/2.17in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories




Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint M6 ø16mm	118-1917	118-1918
Bolt joint ø1/4" ø16mm	118-1946	–
Bolt joint ø1/4" ø19mm	118-1949	–
Snap-on ø7,3 ø16mm	118-1947	118-1919

Model

SC15G

Configuration 1

Sales code:

104G7555

Configuration

Motor configuration	CSIR
Power supply (nominal)	115 V/60 Hz 1~
Refrigerant	R134a
Application	LBP+MBP+HBP
Voltage range	103-127 V
Starting torque	HST
Approvals	UL
Starting device type	relay
Run capacitor	-/-
Start capacitor	240 µF
LRA (locked rotor amps / 4s/ U(N))	39.7 A
RLA (rated load amps / 1s/ U(N))	7.6 A
Cut in current (U(N))	39.7 A

Ambient/ machine room temperatures minimum /maximum


Ambient temperature range: 10 - 43°C / 50 - 109°F

Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling

fan 1,5m/s

Electrical Accessories / Wiring Diagram



[View full size](#)

Components (already pre-assembled)

a2 relay 117U6020

c start capacitor (240µF) 117U5023

d cord relief 103N1004

b plastic cover 103N2008

Alternative components



a2 relay 117U6020

c start capacitor (240µF, 15kOhm) 117U5034

d cord relief 103N1004

b plastic cover 103N2008

Operation Pressure Range



Model
SC15G

Configuration 1

Sales code:
104G7555

Standard Conditions

R134a, 115 V/60 Hz, CSIR, fan 1,5m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	m	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-25 -13	55 131	32 89.6	55 131	256	874	220	0.84	2.86	305	4.92	6.11	CECOMAF LBP
-35 -31	40 104	20 68	40 104	146	496	125	0.70	2.40	207	4.55	3.18	EN12900 LBP
-10 14	55 131	32 89.6	55 131	685	2338	589	1.32	4.50	519	6.06	16.52	CECOMAF MBP
-10 14	45 113	20 68	45 113	781	2664	672	1.57	5.37	496	5.91	18.21	EN12900 MBP
5 41	55 131	32 89.6	55 131	1349	4604	1160	1.83	6.25	737	7.62	33.14	CECOMAF HBP
5 41	50 122	20 68	50 122	1377	4699	1184	1.94	6.61	710	7.41	34.54	EN12900 HBP

Performance Tables

R134a, 115 V/60 Hz, CSIR, fan 1,5m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	m
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-25	-13	324	1104	278	1.03	3.52	314	4.93	7.00
-20	-4	459	1567	395	1.23	4.19	374	5.22	9.96
-15	5	621	2119	534	1.43	4.87	435	5.54	13.51
-10	14	809	2760	696	1.63	5.56	496	5.91	17.66
-5	23	1023	3489	880	1.83	6.25	558	6.31	22.44
0	32	1263	4308	1086	2.04	6.95	620	6.74	27.86
5	41	1529	5217	1315	2.24	7.64	683	7.20	33.96
10	50	1821	6214	1566	2.44	8.33	746	7.69	40.76

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-25	-13	256	874	220	0.84	2.86	305	4.92	6.11
-20	-4	373	1273	321	0.99	3.38	376	5.25	8.92
-15	5	516	1761	444	1.15	3.94	447	5.63	12.39
-10	14	685	2338	589	1.32	4.50	519	6.06	16.52
-5	23	880	3004	757	1.49	5.08	591	6.54	21.34
0	32	1102	3760	948	1.66	5.66	664	7.06	26.87
5	41	1349	4604	1160	1.83	6.25	737	7.62	33.14
10	50	1623	5538	1396	2.00	6.84	810	8.21	40.21