

Model

Designation	SCE21MNIX	220-240V/60Hz 1~	Sales code:	104H8151
-------------	------------------	-------------------------	-------------	-----------------

Compressor design

Oil type	Polyolester	Refrigerant(s)	R290, 0, 0
Oil viscosity	32cSt	Displacement	21cm ³ / 1,28cu.in
Oil quantity	500cm ³ / 16,9fl.oz	Compressors on pallet	48
Refr. charge - tech. limit	500g / 17,6oz		
Free gas volume comp.	3150cm ³ / 106,5fl.oz		
Weight	14,9kg / 32,8lbs		
Motor protection	1# internal		
Winding resistance main	2,2Ω (at 25°C)		
Winding resistance aux	5,3Ω (at 25°C)		
Max. winding temp.	125°C / 257°F		
Max. discharge temp.	140°C / 284°F		



General - Configurations with SCE21MNIX

Conf. 1

Motor configuration	CSCR
Power supply (nominal)	220-240V/60Hz
Number of phases	1
Voltage range	195-254V
Approvals	
Starting torque	HST
Note	Starter kit(relay), cover and cord relief are included and pre-assembled.

Applications with SCE21MNIX

Conf. 1

Refrigerant	R290
Application	MBP
System cooling	fan 3m/s
Hot gas defrost	OK
Long interval pull down	OK

Electrical data - Configurations with SCE21MNIX


Conf. 1

Starting device type	relay
Run capacitor	15μF
Start capacitor	60μF
LRA (locked rotor amps / 4s/ U(N))	31,8A
RLA (rated load amps / 1s/ U(N))	4A
Cut in current (U(N))	

Model			
Designation	SCE21MNIX	220-240V/60Hz 1~	Sales code: 104H8151

Compressor dimensions


Housing	A Height	236,4mm / 9,31in	
	B Height	230,6mm / 9,08in	
	C Length shell	217mm / 8,54in	
	D Length w. cover	263,4mm / 10,37in	
	E Width	161,1mm / 6,34in	
	F Width with equipment	199mm / 7,83in	
Connectors	Suction	Discharge	Process
	X	Y	Z
Diameter [mm]	øi 9,54-9,72	øi 6,41-6,59	øi 6,41-6,59
(i:inside, o:outside) [in]	øi 0,38-0,38	øi 0,25-0,26	øi 0,25-0,26
Material	copper	copper	copper
Horizontal angle ±2°	37°	37°	37°
Vertical angle ±2°	36°	0°	36°
Position l/h/w [mm]	-111/212/57	116/127/81	110/94/72
	[in] -4,4/8,3/2,2	4,5/5/3,2	4,3/3,7/2,8
Straight tube l. [mm]	12	12	12
	[in] 0,5	0,5	0,5




Compressor fixation

	Baseplate [mm] [inch]	
	BI	204 8.03
	Bw	150 5.9
	øE	ø 9.7 ø 0.38
	Large holes [mm] [inch]	
	LI	165 6.5
	Lw	101.6 4
	øL	ø 19 ø 0.75
	Small holes [mm] [inch]	
	SI	170 6.7
	Sw	70 2.76
	øS	ø 16 ø 0.63
	QI	127 5
	Qw	127 5

Bolt joint



Snap-on



Mounting accessories	one comp.	multi pack
Bolt joint M6 ø16mm	118-1917	118-1918
Bolt joint ø1/4" ø16mm	118-1946	
Bolt joint ø1/4" ø19mm	118-1949	
Snap-on ø7,3 ø16mm	118-1947	118-1919

Application notes

Provision for PE Grounding is located at the PE Stamp on the compressor



Model					
Designation	SCE21MNIX	220-240V/60Hz	Conf. 1	Sales code:	104H8151

Configuration	Electrical accessories / wiring diagram				
Motor configuration	CSCR				
Power supply (nominal)	220-240V/60Hz 1~				
Refrigerant	R290				
Application	MBP				
Voltage range	195-254V				
Starting torque	HST				
Approvals					

Ambient/ machine room temperatures minimum /maximum

Ambient temperature range:	10 - 43°C / 50 - 110°F
Machine room temperature range:	10 - 48°C / 50 - 119°F
Compressor cooling:	fan 3m/s

Operation pressure range



Components (Starter kit (a5)+cover (b) +cord relief (d): pre assembled)		
a5	SC starter kit	117U8102
b	cover terminal board + clamp	117U1036
c	start capacitor (60µF)	117U5351
e	run capacitor (15µF, 6.3mm)	117-7167
e1	retaining clamp	117-0313
	screw M4x8mm	117-0301
d	cord relief	103N1007

Model

Designation **SCE21MNIX** **220-240V/60Hz** Conf. 1 Sales code: **104H8151**

Optimization + standard conditions

R290, 230V/60Hz, CSCR, fan 3m/s,

Evaporating pressure (saturation temperature)					Condensing pressure (saturation temperature)						Power consumption			
											Current consumption			
											Ref. mass flow			