

DLX8.7KK.1 High Energy-optimized Compressor R600a 220-240V 50Hz

General

| | |
|-----------------------|-----------------------------|
| Code number | 102H4982 |
| Approvals | EN 60335-2-34 with Annex AA |
| Compressors on pallet | 100 |

Application

| Application | LBP | | |
|--|-----|------------|----|
| Frequency | Hz | 50 | 60 |
| Evaporating temperature | °C | -35 to -10 | - |
| Voltage range | V | 198 - 254 | - |
| Max. condensing temperature continuous (short) | °C | 60 (70) | - |
| Max. winding temperature continuous (short) | °C | 105 (115) | - |

Cooling requirements

| Frequency | Hz | 50 | | | 60 | | |
|-------------------------|----|-----|-----|-----|-----|-----|-----|
| Application | | LBP | MBP | HBP | LBP | MBP | HBP |
| 32°C | | S | - | - | - | - | - |
| 38°C | | S | - | - | - | - | - |
| 43°C | | S | - | - | - | - | - |
| Remarks on application: | | | | | | | |

Motor


| Motor type | RSCR | | |
|---|------|------|------|
| LRA (rated after 4 sec. UL984), HST LST | A | - | 3.1 |
| Cut in Current, HST LST | A | - | 6.1 |
| Resistance, main start winding (25°C) | Ω | 20.2 | 22.8 |

Design

| | | |
|-------------------------------------|-----------------|---------------|
| Displacement | cm ³ | 8.67 |
| Oil quantity (type) | cm ³ | 155 (mineral) |
| Maximum refrigerant charge | g | 150 |
| Free gas volume in compressor | cm ³ | 1400 |
| Weight without electrical equipment | kg | 9.3 |


Dimensions

| | | | |
|--------------------------------------|--------------------------|----|---|
| Height | mm | A | 175 |
| | | B | 169 |
| | | B1 | - |
| | | B2 | - |
| Suction connector | location/I.D. mm angle | C | 6.2 18° |
| | material comment | | Copper Rubber plug |
| Process connector | location/I.D. mm angle | D | 4.5 60° |
| | material comment | | Copper Rubber plug |
| Discharge connector | location/I.D. mm angle | E | 5.0 25° |
| | material comment | | Copper Rubber plug |
| Oil cooler connector | location/I.D. mm angle | F | - |
| | material comment | | - |
| Connector tolerance | I.D. mm | | ±0.09, on 5.0 +0.12/+0.22 on 4.5 +0.10/-0.20 |
| Remarks: With evaporator tray holder | | | |



Yellow warning label

- S = Static cooling normally sufficient
- O = Oil cooling
- F₁ = Fan cooling 1.5 m/s
(compressor compartment temperature equal to ambient temperature)
- F₂ = Fan cooling 3.0 m/s necessary
- SG = Suction gas cooling normally sufficient
- = not applicable in this area




EN 12900 Household (CECOMAF) 220V, 50Hz, RC 2.5 µF, ePTC consumption incl., static cooling

| | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|------|------|------|-------|------|------|------|------|----|---|---|-----|----|----|----|
| Evap. temp. in °C | -45 | -40 | -35 | -30 | -25 | -23.3 | -20 | -15 | -10 | -6.7 | -5 | 0 | 5 | 7.2 | 10 | 15 | 20 |
| Capacity in W | | | 62.1 | 85 | 113 | 124 | 146 | 186 | 232 | | | | | | | | |
| Power cons. in W | | | 55.0 | 65.6 | 76.4 | 79.6 | 87.0 | 98.0 | 111 | | | | | | | | |
| Current cons. in A | | | 0.26 | 0.31 | 0.36 | 0.38 | 0.41 | 0.46 | 0.52 | | | | | | | | |
| COP in W/W | | | 1.13 | 1.30 | 1.48 | 1.55 | 1.69 | 1.89 | 2.10 | | | | | | | | |

ASHRAE LBP 220V, 50Hz, RC 2.5 µF, ePTC consumption incl., static cooling

| | | | | | | | | | | | | | | | | | |
|--------------------|-----|-----|------|------|------|-------|------|------|------|------|----|---|---|-----|----|----|----|
| Evap. temp. in °C | -45 | -40 | -35 | -30 | -25 | -23.3 | -20 | -15 | -10 | -6.7 | -5 | 0 | 5 | 7.2 | 10 | 15 | 20 |
| Capacity in W | | | 76.1 | 104 | 138 | 151 | 179 | 227 | 284 | | | | | | | | |
| Power cons. in W | | | 55.2 | 65.7 | 75.9 | 80.3 | 86.0 | 98.0 | 110 | | | | | | | | |
| Current cons. in A | | | 0.26 | 0.31 | 0.36 | 0.38 | 0.41 | 0.46 | 0.52 | | | | | | | | |
| COP in W/W | | | 1.38 | 1.59 | 1.82 | 1.88 | 2.07 | 2.32 | 2.57 | | | | | | | | |



| Accessories for | DLX8.7KK.1 | Figure | Code number | Test conditions | EN 12900/ CECOMAF | ASHRAE LBP |
|--------------------------------------|-------------------------|--------|-------------|-----------------------------|----------------------|------------|
| PTC starting device | 6.3 mm spade connectors | a1 | 103N0016 | Condensing temperature | 55°C | 54.4°C |
| | 4.8 mm spade connectors | | 103N0021 | Ambient temperature | 32°C | 32°C |
| ePTC starting device | 4.8 mm spade connectors | | 103N0055 | Suction gas temperature | 32°C | 32°C |
| Cover | | b | 103N0491 | Liquid temperature | no subcooling | 32°C |
| Run capacitor 2.5 µF (compulsory) | 6.3 mm spade connectors | e | — | Mounting accessories | | |
| | 4.8 mm spade connectors | | 117-7139 | Code number | | |
| Cord relief | | d | 103N1010 | Bolt joint for one comp. | Ø: 16 mm | 118-1917 |
| Protection screen for PTC | | g | 103N0476 | Bolt joint in quantities | Ø: 16 mm | 118-1918 |
| | | | | Snap-on in quantities | Ø: 16 mm | 118-1919 |

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without subsequential changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved. www.secop.com