

R290 · 220-240V | 50 Hz

A NEW PREMIUM PROPANE SOLUTION FOR GREEN AND EFFICIENT CABINETS


SECCP



KL-Series



Commercial
Applications



New Hermetic
Terminal Plug



Broad Application
Range (LBP & MBP)



Optimal Energy
Consumption



Reduced Noise
and Vibration



R290
Green Refrigerant

- **Premium Robustness**
The KL-Series features the tried and trusted quality of our K-Series optimized for light commercial applications
- **Robust Solution for Food Retail and Food Service Applications**
Dedicated reliable design for bottle coolers, glass door merchandisers, and ice cream freezers (LBP and MBP applications) and suitable for food service applications
- **Superior Efficiency**
High COP and top efficiency for light commercial applications with low GWP refrigerant propane (R290)
- **Innovative Solution for Flammable Refrigerants**
Including a patented solution to increase robustness using propane that has been subject to extensive testing at Secop
- **Easier Application Assembly**
New terminal board design for additional interconnections
- **Reduced Noise Level**
Improved noise and reduced vibration, a new benchmark level for hydrocarbon refrigerants

Secop's new **KL-Series** is based on the very successful K-Series, Secop's core product for residential applications, with more than 50 million units installed. The KL-Series was developed to offer a reliable, top performing, and cost-effective solution for the next generation of light commercial cabinets using environmentally friendly refrigerant propane and offering high energy efficiency.

Secop has developed a robust series for commercial refrigeration, which integrates various technical innovations, such as a noise-reducing shell, robust suspension, a robust internal discharge tube, improved valves, optimized motors, and a new muffler for lower noise levels when using propane. The KL-Series comes with a patented hermetic terminal plug designed to increase robustness for usage with flammable refrigerants.

The KL-Series offers a reliable and robust design for commercial applications, specifically designed for R290 hydrocarbon refrigerant. This is the latest improvement on Secop's products for flammable refrigerants and will set a benchmark in the entire industry.

General	KLF4.0CND	KLF4.8CND	KLF5.6CND	KLF6.6CND	KLF7.7CND	KLF8.6CND
Compressor	106H2401	106H2500	106H2600	106H2700	106H2800	106H2900
Compressor with pre-assembled start equipment	106H2411	106H2510	106H2610	106H2710	106H2810	106H2910
Approvals	VDE, CCC	VDE, CCC	VDE, CCC	VDE, CCC	VDE, CCC	VDE

Application	R290					
Application	LBP/MBP	LBP/MBP	LBP/MBP	LBP/MBP	LBP/MBP	LBP/MBP
Evaporating temperature	°C	-40 to 7.2	-40 to 7.2	-40 to 7.2	-35 to 7.2	-35 to 7.2
Voltage range / frequency	V/Hz	198-254/50	198-254/50	198-254/50	198-254/50	198-254/50


Performance Data ASHRAE LBP (220 V, 50 Hz • fan cooling)						
Evaporating temperature	°C	-23.3	-23.3	-23.3	-23.3	-23.3
Cooling capacity	W	183	230	274	337	456
Power consumption	W	124	153	177	223	284
COP	W/W	1.48	1.50	1.55	1.51	1.61
Test conditions	Condensing temperature: 54.4 °C Suction gas temperature: 32.2 °C Ambient temperature: 32.2 °C Liquid temperature: 32.2 °C					

Performance Data ASHRAE MBP (220 V, 50 Hz • fan cooling)						
Evaporating temperature	°C	-6.7	-6.7	-6.7	-6.7	-6.7
Cooling capacity	W	336	410	495	596	688
Power consumption	W	162	199	239	296	343
COP	W/W	2.08	2.06	2.07	2.01	2.00
Test conditions	Condensing temperature: 54.4 °C Suction gas temperature: 35 °C Ambient temperature: 32.2 °C Liquid temperature: 46.1 °C					

Performance Data ASHRAE MBP (220 V, 50 Hz • fan cooling • run capacitor)						
Evaporating temperature	°C	-6.7	-6.7	-6.7	-6.7	-6.7
Cooling capacity	W	337	411	501	598	694
Power consumption	W	157	190	231	282	327
COP	W/W	2.14	2.17	2.17	2.12	2.14
Test conditions	Condensing temperature: 54.4 °C Suction gas temperature: 35 °C Ambient temperature: 32.2 °C Liquid temperature: 46.1 °C					

Dimensions			
Height	mm	A	182 174*
		B	175 164*
Suction connector	I.D. mm angle material seal	C	8.2 30° Copper Rubber plug
Process connector	I.D. mm angle material seal	D	6.2 35° Copper Rubber plug
Discharge connector	I.D. mm angle material seal	E	6.2 40° Copper Rubber plug
Connector tolerance	I.D. mm		±0.09

*Applicable for the variants KLF4.0CND (106H2408) & KLF4.8CND (106H2508, 106H2518) with lower top cover
Variants with small baseplates available on request, please contact Secop for further information



Secop GmbH · Lise-Meitner-Str. 29 · 24941 Flensburg, Germany · Tel: +49 461 4941 0 · www.secop.com

Secop accepts no responsibility for possible errors in catalogs, brochures, and other printed material. Secop reserves the right to alter its products without notice. This also applies to products already on order provided that such alterations can be made without consequential changes being necessary to specifications already agreed. All trademarks in this material are the property of the respective companies. Secop and the Secop logotype are trademarks of Secop GmbH. All rights reserved.