Singolo
Imballi

Single Pack NLE11CNL 115-127V 60Hz CSIR

Codice Imballo Singolo: **195B4305**

Posizione	Titolo	Codice	Quantità
1	Compressor NLE11CNL	105H5983	1
2	Bolt joint for one compressor | M6 | ø16mm	118-1917	1
Below electrical equipment is pre-assembled on the compressor:			
3	Starting relay	117U7020	1
4	Starting capacitor (180µF 125V, 6.3mm)	117U5039	1
5	Cable clamp	103N0489	1
6	Cover	103N2011	1
7	Yoke	103N0126	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop non si assume alcuna responsabilità per eventuali errori presenti in cataloghi, brochure e altro materiale stampato. Secop si riserva il diritto di modificare i propri prodotti senza preavviso. Ciò vale anche per i prodotti già ordinati, a condizione che tali modifiche possano essere apportate senza che siano necessarie modifiche successive alle specifiche già concordate. Tutti i marchi presenti in questo materiale sono di proprietà delle rispettive aziende. Secop e il logo Secop sono marchi di Secop GmbH. Tutti i diritti sono riservati.

Model
NLE11CNL

Sales code:
105H5983

Compressor Data

Refrigerant(s)	**R290**
Refr. charge - tech. limit	**400g / 14.11oz**
Weight	**12.14 kg / 26.76lbs**
Displacement	**11.15 cm3 / 0.68cu.in**
Compressors on pallet	**80**

General – Configurations With NLE11CNL

–	**Conf. 1**
Motor configuration	CSIR
Power supply (nominal)	115 V/60 Hz
Number of phases	1
Voltage range	95-135 V
Approvals	UL, CCC
Starting torque	HST
Refrigerant	R290
Application	LBP
Hot gas defrost	OK

Application Notes

- Electrical equipment is included and pre-assembled to compressor.
- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
NLE11CNL

Sales code:
105H5983

Compressor Design

Oil type	**32 cSt POE RL32DR**	Winding resistance main	**1.1 Ohm**
Oil viscosity	**32cSt**	Winding resistance aux	**3.61 Ohm**
Oil quantity	**298 / 10.08fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**2,360 cm3 / 79.80fl.oz**	Max. discharge temp.	**130°C / 266°F**
Motor protection	**internal**		

Compressor Dimensions

Housing

A Height	**203mm / 7.99in**
B Height	**197mm / 7.76in**
C Length shell	**205mm / 8.07in**
D Length w. cover	**254mm / 10.00in**
E Width	**166mm / 6.54in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.41–6.59 / 0.25–0.26in	øi 6.41–6.59 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	0°	0°	0°
Vertical angle ±2°	15°	21°	155°
Position l/h/w [mm]	132/68.5/56.7 / 5.20/2.70/2.23in	94/101.7/81 / 3.70/4.00/3.19in	-109.3/94.3/72 / -4.30/3.71/2.83in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Bolt joint | ø1/4" | ø19mm	118-1949	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
NLE11CNL Configuration 1

Sales code:
105H5983

Configuration

Motor configuration	**CSIR**
Power supply (nominal)	**115 V/60 Hz 1~**
Refrigerant	**R290**
Application	**LBP**
Voltage range	**95-135 V**
Starting torque	**HST**
Approvals	**UL, CCC**
Starting device type	**relay**
Run capacitor	**-/-**
Start capacitor	**180 µF**
LRA (locked rotor amps / 4s/ U(N))	**28.67 A**
RLA (rated load amps / 1s/ U(N))	**5.74 A**
Cut in current (U(N))	**28.67 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components (already pre-assembled)
a2 relay 117U7020
c start capacitor (180µF) 117U5039
b plastic cover 103N2011
d cord relief 103N1010

Operation Pressure Range





Model

NLE11CNL Configuration 1

Sales code:

105H5983

Standard Conditions

R290, 115 V/60 Hz, CSIR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**674**	2301	580	**1.63**	5.56	414	4.80	6.85	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**502**	1714	432	**1.26**	4.30	398	4.68	6.30	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**384**	1312	331	**1.29**	4.40	298	4.04	4.41	**EN12900 LBP**
-23.3 -10	48.8 119.8	4.4 39.9	48.8 119.8	**547**	1866	470	**1.35**	4.62	404	4.73	7.59	**ARI540 LBP**
-23.3 -10	40.6 105.1	32.2 90	32.2 90	**725**	2475	624	**1.89**	6.45	384	4.61	7.37	**AHAM LBP**
-35 -31	45 113	32 89.6	45 113	**366**	1250	315	**1.22**	4.18	300	4.05	4.13	**opt LBP**

Performance Tables

R290, 115 V/60 Hz, CSIR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-35	-31	**366**	1250	315	**1.22**	4.18	300	4.05	4.13
-30	-22	**465**	1586	400	**1.36**	4.64	342	4.29	5.25
-25	-13	**588**	2007	506	**1.54**	5.25	382	4.57	6.67
-20	-4	**734**	2506	632	**1.74**	5.95	421	4.88	8.36
-15	5	**902**	3078	776	**1.96**	6.68	461	5.21	10.31
-10	14	**1089**	3717	937	**2.17**	7.39	503	5.53	12.51

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-35	-31	**310**	1057	267	**1.05**	3.59	294	4.07	3.86
-30	-22	**394**	1345	339	**1.13**	3.87	348	4.35	4.93
-25	-13	**502**	1714	432	**1.26**	4.30	398	4.68	6.30
-20	-4	**632**	2156	543	**1.41**	4.82	447	5.06	7.95
-15	5	**781**	2665	672	**1.58**	5.38	496	5.46	9.88
-10	14	**948**	3236	816	**1.74**	5.93	546	5.87	12.06



NL Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

RSIR





CSIR





RSCR







NL Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



Brazing on Suction Connectors (Direct Intake)

representative image



! max. 150°C/302°F ! at socket

brazing solder: phosphor (LP7) or silver

Refer to Product Bulletin:
Brazing on Suction Connectors (Compressors with Direct Suction Intake)

Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**