Singolo
Imballi

Single Pack SC21FTX 220-240V 50Hz CSIR

Codice Imballo Singolo: **195B4498**

Posizione	Titolo	Codice	Quantità
1	Compressor SC21FTX	104G8105	1
2	Starting relay	117U6019	1
3	Starting capacitor (80µF 220V, 6.3mm)	117U5017	1
4	Cord relief	103N1004	1
5	Cover	103N2009	1
6	Bolt joint for one compressor | M6 | ø16mm	118-1917	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop non si assume alcuna responsabilità per eventuali errori presenti in cataloghi, brochure e altro materiale stampato. Secop si riserva il diritto di modificare i propri prodotti senza preavviso. Ciò vale anche per i prodotti già ordinati, a condizione che tali modifiche possano essere apportate senza che siano necessarie modifiche successive alle specifiche già concordate. Tutti i marchi presenti in questo materiale sono di proprietà delle rispettive aziende. Secop e il logo Secop sono marchi di Secop GmbH. Tutti i diritti sono riservati.

Model
SC21FTX

Sales code:
104G8105

Compressor Data

Refrigerant(s)	**R134a**
Refr. charge - tech. limit	**1300g / 45.86oz**
Weight	**13.70 kg / 30.20lbs**
Displacement	**20.95 cm3 / 1.28cu.in**
Compressors on pallet	**80**

General – Configurations With SC21FTX

–	**Conf. 1**
Motor configuration	CSIR
Power supply (nominal)	220-240 V/50 Hz
Number of phases	1
Voltage range	187-254 V
Approvals	CCC, VDE, EAC
Starting torque	HST
Refrigerant	R134a
Application	LBP
Hot gas defrost	OK
Long interval pull down	OK

Application Notes

- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
SC21FTX

Sales code:
104G8105

Compressor Design

Oil type	**POE**	Winding resistance main	**3.7 Ohm**
Oil viscosity	**22cSt**	Winding resistance aux	**14 Ohm**
Oil quantity	**550 / 18.60fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**1,460 cm3 / 49.37fl.oz**	Max. discharge temp.	**135°C / 275°F**
Motor protection	**internal**		

Compressor Dimensions

Housing

A Height	**219mm / 8.62in**
B Height	**213mm / 8.39in**
C Length shell	**218mm / 8.58in**
D Length w. cover	**255mm / 10.04in**
E Width	**151mm / 5.94in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 10.11–10.29 / 0.40–0.41in	øi 6.11–6.29 / 0.24–0.25in	øi 6.11–6.29 / 0.24–0.25in
Material	CU	CU	CU
Horizontal angle ±2°	37°	37°	143°
Vertical angle ±2°	30°	0°	150°
Position l/h/w [mm]	107/193/55 / 4.21/7.60/2.17in	115/110/63 / 4.53/4.33/2.48in	-107/193/55 / -4.21/7.60/2.17in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Bolt joint | ø1/4" | ø19mm	118-1949	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
SC21FTX Configuration 1

Sales code:
104G8105

Configuration

Motor configuration	**CSIR**
Power supply (nominal)	**220-240 V/50 Hz 1~**
Refrigerant	**R134a**
Application	**LBP**
Voltage range	**187-254 V**
Starting torque	**HST**
Approvals	**CCC, VDE, EAC**
Starting device type	**relay**
Run capacitor	**-/-**
Start capacitor	**80 µF**
RLA (rated load amps / 1s/ U(N))	**-/-A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components
a2 relay 117U6019
c start capacitor (80µF) 117U5017
d cord relief 103N1004
b plastic cover 103N2009

Operation Pressure Range





Model
SC21FTX Configuration 1

Sales code:
104G8105

Standard Conditions

R134a, 220 V/50 Hz, CSIR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**568**	1939	489	**1.26**	4.32	449	3.20	11.03	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**415**	1416	357	**0.97**	3.31	428	3.12	9.90	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**281**	960	242	**0.89**	3.04	316	2.72	6.15	**EN12900 LBP**
-23.3 -10	48.8 119.8	4.4 39.9	48.8 119.8	**474**	1616	407	**1.06**	3.62	446	3.20	12.43	**ARI540 LBP**
-23.3 -10	40.6 105.1	32.2 90	32.2 90	**636**	2170	547	**1.47**	5.02	433	3.16	12.34	**AHAM LBP**
-35 -31	45 113	32 89.6	45 113	**260**	886	223	**0.83**	2.82	314	2.71	5.59	**opt LBP**

Performance Tables

R134a, 220 V/50 Hz, CSIR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-35	-31	**260**	886	223	**0.83**	2.82	314	2.71	5.59
-30	-22	**367**	1252	316	**0.99**	3.38	370	2.90	7.92
-25	-13	**499**	1704	429	**1.18**	4.03	423	3.11	10.80
-20	-4	**661**	2254	568	**1.39**	4.73	477	3.34	14.32
-15	5	**855**	2917	735	**1.61**	5.49	531	3.58	18.60
-10	14	**1086**	3706	934	**1.84**	6.28	590	3.83	23.72
-5	23	**1358**	4635	1168	**2.08**	7.09	654	4.10	29.80

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-35	-31	**192**	655	165	**0.65**	2.22	296	2.66	4.56
-30	-22	**296**	1010	255	**0.81**	2.77	364	2.88	7.04
-25	-13	**415**	1416	357	**0.97**	3.31	428	3.12	9.90
-20	-4	**553**	1886	475	**1.13**	3.85	490	3.37	13.22
-15	5	**713**	2434	614	**1.30**	4.42	551	3.64	17.13
-10	14	**901**	3074	775	**1.47**	5.01	613	3.92	21.72
-5	23	**1119**	3818	962	**1.65**	5.63	679	4.22	27.12



SC Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

RSIR





CSIR





CSCR







SC Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



CSCR



Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**