Singolo
Imballi

Single Pack SCE25LNDX 220-240V 50Hz CSCR

Codice Imballo Singolo: **195B4786**

Posizione	Titolo	Codice	Quantità
1	Compressor SCE25LNDX	104H8420	1
2	Run Capacitor (10µF 450V, 6.3mm)	117-7166	1
3	Starting capacitor (60µF 260V, 6.3mm)	117U5351	1
4	Run capacitor bracket	117-0313	1
5	Screw for bracket M4x8mm	117-0301	1
6	Bolt joint for one compressor | M6 | ø16mm	118-1917	1
Below electrical equipment is pre-assembled on the compressor:			
7	SCE starting device	117U8101	1
8	Cover with clamp	117U1036	1
9	Cord relief	103N1007	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop non si assume alcuna responsabilità per eventuali errori presenti in cataloghi, brochure e altro materiale stampato. Secop si riserva il diritto di modificare i propri prodotti senza preavviso. Ciò vale anche per i prodotti già ordinati, a condizione che tali modifiche possano essere apportate senza che siano necessarie modifiche successive alle specifiche già concordate. Tutti i marchi presenti in questo materiale sono di proprietà delle rispettive aziende. Secop e il logo Secop sono marchi di Secop GmbH. Tutti i diritti sono riservati.

Model
SCE25LNDX

Sales code:
104H8420

Compressor Data

Refrigerant(s)	**R290**
Refr. charge - tech. limit	**500g / 17.64oz**
Weight	**14.90 kg / 32.85lbs**
Displacement	**25.00 cm3 / 1.53cu.in**
Compressors on pallet	**48**

General – Configurations With SCE25LNDX

–	**Conf. 1**
Motor configuration	CSCR
Power supply (nominal)	220-240 V/50 Hz
Number of phases	1
Voltage range	198-254 V
Approvals	VDE, CCC, CB
Starting torque	HST
Refrigerant	R290
Application	LBP
Hot gas defrost	OK

Application Notes

- Starter kit(relay), cover and cord relief are included and pre-assembled.
- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
SCE25LNDX

Sales code:
104H8420

Compressor Design

Oil type	**POE**	Winding resistance main	**3.3 Ohm**
Oil viscosity	**32cSt**	Winding resistance aux	**10.8 Ohm**
Oil quantity	**500 / 16.91fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**3,150 cm3 / 106.51fl.oz**	Max. discharge temp.	**140°C / 284°F**
Motor protection	**internal**		

Compressor Dimensions

Housing

A Height	**236.4mm / 9.31in**
B Height	**230.6mm / 9.08in**
C Length shell	**217mm / 8.54in**
D Length w. cover	**263.4mm / 10.37in**
E Width	**161.1mm / 6.34in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 12.81–12.99 / 0.50–0.51in	øi 8.11–8.29 / 0.32–0.33in	øi 6.11–6.29 / 0.24–0.25in
Material	CU	CU	CU
Horizontal angle ±2°	37°	37°	37°
Vertical angle ±2°	36°	0°	36°
Position l/h/w [mm]	-110.5/211.8/56.7 / -4.35/8.34/2.23in	115.5/127/81 / 4.55/5.00/3.19in	109.5/94.3/72 / 4.31/3.71/2.83in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Bolt joint | ø1/4" | ø19mm	118-1949	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
SCE25LNDX Configuration 1

Sales code:
104H8420

Configuration

Motor configuration	**CSCR**
Power supply (nominal)	**220-240 V/50 Hz 1~**
Refrigerant	**R290**
Application	**LBP**
Voltage range	**198-254 V**
Starting torque	**HST**
Approvals	**VDE, CCC, CB**
Starting device type	**relay**
Run capacitor	**10 µF**
Start capacitor	**60 µF**
LRA (locked rotor amps / 4s/ U(N))	**22.1 A**
RLA (rated load amps / 1s/ U(N))	**3.7 A**
Cut in current (U(N))	**22.1 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components (Starter kit + cover + cord relief: pre-assembled)
a5 SC starter kit 117U8101
b cover terminal board + clamp 117U1036
c start capacitor (60µF) 117U5351
e run cap (10µF, 6.3mm,c.length 280mm) 117-7166
e1 retaining clamp 117-0313
screw M4x8mm 117-0301
d cord relief 103N1007

Operation Pressure Range





Model
SCE25LNDX Configuration 1

Sales code:
104H8420

Standard Conditions

R290, 220 V/50 Hz, CSCR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**1182**	4033	1017	**1.62**	5.54	728	3.56	12.01	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**881**	3005	757	**1.26**	4.30	699	3.44	11.04	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**676**	2308	582	**1.26**	4.30	537	2.75	7.76	**EN12900 LBP**
-23.3 -10	48.8 119.8	4.4 39.9	48.8 119.8	**971**	3313	835	**1.37**	4.67	709	3.48	13.48	**ARI540 LBP**
-23.3 -10	40.6 105.1	32.2 90	32.2 90	**1313**	4480	1129	**1.91**	6.53	686	3.38	13.34	**AHAM LBP**
-35 -31	45 113	32 89.6	45 113	**642**	2191	552	**1.18**	4.02	546	2.79	7.24	**opt LBP**

Performance Tables

R290, 220 V/50 Hz, CSCR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-40	-40	**470**	1604	404	**0.97**	3.30	486	2.56	5.29
-35	-31	**642**	2191	552	**1.18**	4.02	546	2.79	7.24
-30	-22	**837**	2854	719	**1.37**	4.68	610	3.06	9.45
-25	-13	**1057**	3608	909	**1.56**	5.33	676	3.34	11.98
-20	-4	**1307**	4461	1124	**1.76**	6.00	744	3.63	14.87
-15	5	**1590**	5424	1367	**1.97**	6.70	809	3.92	18.16
-10	14	**1908**	6511	1641	**2.19**	7.48	871	4.20	21.91
-5	23	**2266**	7731	1949	**2.44**	8.34	927	4.45	26.17

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-40	-40	**393**	1342	338	**0.84**	2.85	470	2.48	4.88
-35	-31	**529**	1805	455	**0.99**	3.37	535	2.74	6.59
-30	-22	**690**	2356	594	**1.13**	3.85	612	3.06	8.62
-25	-13	**881**	3005	757	**1.26**	4.30	699	3.44	11.04
-20	-4	**1103**	3764	949	**1.39**	4.74	794	3.86	13.88
-15	5	**1361**	4643	1170	**1.52**	5.18	896	4.32	17.21
-10	14	**1658**	5655	1425	**1.66**	5.65	1001	4.80	21.08
-5	23	**1996**	6811	1717	**1.80**	6.15	1108	5.29	25.55



SCE & SCE Plus Compressors

Optimized Electrical CSCR System

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

CSCR







SCE & SCE Plus Compressors

Optimized Electrical CSCR System

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**