Singolo
Imballi

Single Pack KLE6.6GFHX 115-127V 60Hz CSIR

Codice Imballo Singolo: **195B4801**

Posizione	Titolo	Codice	Quantità
1	Compressor KLE6.6GFHX	106G6713	1
2	Bolt joint for one compressor | M6 | ø16mm	118-1917	1
Below electrical equipment is pre-assembled on the compressor:			
3	Starting relay (QLZ-11.6A, overload protector T1246/L6)	117U7080	1
4	Starting capacitor (240µF 125V, 6.3mm)	117U5002	1
5	Cable clamp	16058100	1
6	Screw for cable clamp	10636000	1
7	Screw for cable clamp	10636200	1
8	Cover	10636401	1
9	Earth screw	10641201	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop non si assume alcuna responsabilità per eventuali errori presenti in cataloghi, brochure e altro materiale stampato. Secop si riserva il diritto di modificare i propri prodotti senza preavviso. Ciò vale anche per i prodotti già ordinati, a condizione che tali modifiche possano essere apportate senza che siano necessarie modifiche successive alle specifiche già concordate. Tutti i marchi presenti in questo materiale sono di proprietà delle rispettive aziende. Secop e il logo Secop sono marchi di Secop GmbH. Tutti i diritti sono riservati.

Model
KLE6.6GFHX

Sales code:
106G6713

Compressor Data

Refrigerant(s)	**R134a / R513A**
Refr. charge - tech. limit	**300g / 10.58oz**
Weight	**9.50 kg / 20.94lbs**
Displacement	**6.60 cm3 / 0.40cu.in**
Compressors on pallet	**100**

General – Configurations With KLE6.6GFHX

–	**Conf. 1**	**Conf. 2**
Motor configuration	CSIR	CSIR
Power supply (nominal)	115-127 V/60 Hz	115-127 V/60 Hz
Number of phases	1	1
Voltage range	95-140 V	95-140 V
Approvals	UL	UL
Starting torque	HST	HST
Refrigerant	R134a	R513A
Application	LBP+MBP+HBP	LBP+MBP+HBP
Hot gas defrost	OK	OK
Long interval pull down	OK	OK

Application Notes

- Electrical equipment is included and pre-assembled to compressor.
- Provision for PE Grounding is located at the PE Stamp on the compressor
- Suctiongas connector and Process connector can be switched (minor loss of cooling capacity)
- Recommanded voltage range for HBP is 103-140 V/60 Hz
- Good robustness against liquid intake.
- Ice-cube maker optimization - indirect suction intake.

Model
KLE6.6GFHX

Sales code:
106G6713

Compressor Design

Oil type	**POE**	Winding resistance main	**2 Ohm**
Oil viscosity	**19,2cSt**	Winding resistance aux	**5.3 Ohm**
Oil quantity	**200 cm3 / 6.76fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**1,580 cm3 / 53.43fl.oz**	Max. discharge temp.	**130°C / 266°F**
Motor protection	**external**		

Compressor Dimensions

Housing

A Height	**182mm / 7.17in**
B Height	**175mm / 6.89in**
C Length shell	**198mm / 7.80in**
D Length w. cover	**238mm / 9.37in**
E Width	**160mm / 6.30in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.41–6.59 / 0.25–0.26in	øi 6.41–6.59 / 0.25–0.26in
Material	CU	CU	CU
Horizontal angle ±2°	35°	13°	0°
Vertical angle ±2°	30°	40°	145°
Position l/h/w [mm]	119/73/59 / 4.69/2.87/2.32in	117/107/66 / 4.61/4.21/2.60in	-88/101/71 / -3.46/3.98/2.80in
Straight tube l. [mm]	13.5 / 0.53in	13.5 / 0.53in	13.5 / 0.53in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Bolt joint | ø1/4" | ø19mm	118-1949	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
KLE6.6GFHX Configuration 1

Sales code:
106G6713

Configuration

Motor configuration	**CSIR**
Power supply (nominal)	**115-127 V/60 Hz 1~**
Refrigerant	**R134a**
Application	**LBP+MBP+HBP**
Voltage range	**95-140 V**
Starting torque	**HST**
Approvals	**UL**
Starting device type	**relay**
Run capacitor	**-/-**
Start capacitor	**240 µF**
LRA (locked rotor amps / 4s/ U(N))	**31.1 A**
RLA (rated load amps / 1s/ U(N))	**4.3 A**
Cut in current (U(N))	**31.5 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components (already pre-assembled)
a5 current relay (T1246/L6) 117U7080
c start capacitor (240µF) 117U5002
b, d cover + clamp + screws (5VA-compl.) 103N0600

Alternative components
b, d 100x cover + clamp + screws (5VA) 103N2060
b, d cover + clamp + screws (5VA) in bag 103N1060

Operation Pressure Range





Model Sales code:

KLE6.6GFHX Configuration 1 **106G6713**

Standard Conditions

R134a, 120 V/60 Hz, CSIR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**234**	800	202	**1.34**	4.57	175	2.59	4.55	**ASHRAE LBP**
-6.7 20	54.4 129.9	35 95	46.1 115	**481**	1643	414	**1.86**	6.36	258	3.15	10.48	**ASHRAE MBP**
7.2 45	54.4 129.9	35 95	46.1 115	**852**	2908	733	**2.57**	8.77	332	3.72	18.87	**ASHRAE HBP**
-35 -31	40 104	20 68	40 104	**118**	402	101	**0.96**	3.27	123	2.33	2.58	**EN12900 LBP**
-10 14	45 113	20 68	45 113	**419**	1428	360	**1.85**	6.32	226	2.91	9.76	**EN12900 MBP**
5 41	50 122	20 68	50 122	**728**	2485	626	**2.38**	8.11	306	3.52	18.27	**EN12900 HBP**

Performance Tables

R134a, 120 V/60 Hz, CSIR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-32	-26	**134**	456	115	**0.98**	3.35	136	2.38	2.88
-30	-22	**152**	518	131	**1.05**	3.58	145	2.42	3.28
-20	-4	**267**	910	229	**1.44**	4.90	186	2.65	5.79
-10	14	**434**	1479	373	**1.92**	6.55	226	2.91	9.47
0	32	**668**	2278	574	**2.49**	8.50	268	3.23	14.73
10	50	**984**	3357	846	**3.12**	10.66	315	3.59	22.02
15	59	**1178**	4018	1013	**3.45**	11.77	341	3.79	26.61

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-32	-26	**106**	361	91	**0.82**	2.79	129	2.34	2.51
-30	-22	**123**	420	106	**0.88**	3.00	140	2.39	2.93
-20	-4	**228**	780	197	**1.19**	4.06	192	2.69	5.46
-10	14	**375**	1280	323	**1.55**	5.28	242	3.03	9.05
0	32	**579**	1975	498	**1.97**	6.72	294	3.42	14.11
10	50	**854**	2916	735	**2.44**	8.34	350	3.87	21.17
15	59	**1024**	3495	881	**2.70**	9.21	380	4.11	25.64

Model
KLE6.6GFHX Configuration 2

Sales code:
106G6713

Configuration

Motor configuration	**CSIR**
Power supply (nominal)	**115-127 V/60 Hz 1~**
Refrigerant	**R513A**
Application	**LBP+MBP+HBP**
Voltage range	**95-140 V**
Starting torque	**HST**
Approvals	**UL**
Starting device type	**relay**
Run capacitor	**-/-**
Start capacitor	**240 µF**
LRA (locked rotor amps / 4s/ U(N))	**31.1 A**
RLA (rated load amps / 1s/ U(N))	**4.3 A**
Cut in current (U(N))	**31.5 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components (already pre-assembled)
a5 current relay (T1246/L6) 117U7080
c start capacitor (240µF) 117U5002
b, d cover + clamp + screws (5VA-compl.) 103N0600

Alternative components
b, d 100x cover + clamp + screws (5VA) 103N2060
b, d cover + clamp + screws (5VA) in bag 103N1060

Operation Pressure Range





Model

KLE6.6GFHX Configuration 2

Sales code:

106G6713

Standard Conditions

R513A, 120 V/60 Hz, CSIR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**259**	882	222	**1.35**	4.61	192	2.69	5.66	**ASHRAE LBP**
-6.7 20	54.4 129.9	35 95	46.1 115	**504**	1719	433	**1.84**	6.28	274	3.27	12.56	**ASHRAE MBP**
7.2 45	54.4 129.9	35 95	46.1 115	**876**	2989	753	**2.53**	8.63	346	3.85	22.26	**ASHRAE HBP**
-35 -31	40 104	20 68	40 104	**129**	440	111	**0.95**	3.26	135	2.38	3.25	**EN12900 LBP**
-10 14	45 113	20 68	45 113	**435**	1485	374	**1.81**	6.18	240	3.02	11.79	**EN12900 MBP**
5 41	50 122	20 68	50 122	**733**	2500	630	**2.29**	7.82	320	3.63	21.61	**EN12900 HBP**

Performance Tables

R513A, 120 V/60 Hz, CSIR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-32	-26	**148**	504	127	**0.98**	3.34	151	2.45	3.64
-30	-22	**167**	570	144	**1.05**	3.57	160	2.50	4.12
-20	-4	**287**	979	247	**1.43**	4.87	201	2.75	7.12
-10	14	**457**	1558	393	**1.90**	6.48	240	3.02	11.43
0	32	**692**	2360	595	**2.46**	8.40	281	3.32	17.52
10	50	**1007**	3437	866	**3.08**	10.53	327	3.68	25.95
15	59	**1200**	4096	1032	**3.41**	11.62	352	3.89	31.25

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-32	-26	**117**	400	101	**0.81**	2.78	144	2.41	3.23
-30	-22	**135**	462	116	**0.87**	2.97	155	2.47	3.74
-20	-4	**242**	827	208	**1.16**	3.97	208	2.80	6.74
-10	14	**388**	1326	334	**1.50**	5.13	258	3.15	10.90
0	32	**590**	2011	507	**1.91**	6.50	309	3.55	16.76
10	50	**861**	2937	740	**2.36**	8.05	365	4.00	24.93
15	59	**1028**	3506	884	**2.60**	8.86	396	4.25	30.13



KL Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

RSIR





RSCR





CSIR







KL Compressors

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**