Singolo
Imballi

Single Pack NLE15LNDX 220-240V 50Hz CSCR

Codice Imballo Singolo: **195B4836**

Posizione	Titolo	Codice	Quantità
1	Compressor NLE15LNDX	105H7500	1
2	Start equipment NLE	117U8201	1
3	Starting capacitor (80µF 260V)	117U5353	1
4	Run Capacitor (10µF 450V, 6.3mm)	117-7166	1
5	Run capacitor bracket	117-0314	1
6	Cover NLE	117U1038	1
7	Cord relief	103N1007	1
8	Screw for bracket M4x8mm	117-0301	1
9	Bolt joint for one compressor | M6 | ø16mm	118-1917	1

Secop GmbH • Lise-Meitner-Straße 29 • 24941 Flensburg, Germany • Tel: +49 461 4941 0 • **www.secop.com**

Secop non si assume alcuna responsabilità per eventuali errori presenti in cataloghi, brochure e altro materiale stampato. Secop si riserva il diritto di modificare i propri prodotti senza preavviso. Ciò vale anche per i prodotti già ordinati, a condizione che tali modifiche possano essere apportate senza che siano necessarie modifiche successive alle specifiche già concordate. Tutti i marchi presenti in questo materiale sono di proprietà delle rispettive aziende. Secop e il logo Secop sono marchi di Secop GmbH. Tutti i diritti sono riservati.

Model
NLE15LNDX

Sales code:
105H7500

Compressor Data

Refrigerant(s)	**R290**
Refr. charge - tech. limit	**300g / 10.58oz**
Weight	**11.80 kg / 26.01lbs**
Displacement	**14.60 cm3 / 0.89cu.in**
Compressors on pallet	**80**

General – Configurations With NLE15LNDX

–	**Conf. 1**
Motor configuration	CSCR
Power supply (nominal)	220-240 V/50 Hz
Number of phases	1
Voltage range	198-254 V
Approvals	VDE
Starting torque	HST
Refrigerant	R290
Application	LBP
Hot gas defrost	OK

Application Notes

- Provision for PE Grounding is located at the PE Stamp on the compressor

Model
NLE15LNDX

Sales code:
105H7500

Compressor Design

Oil type	**POE**	Winding resistance main	**7.1 Ohm**
Oil viscosity	**32cSt**	Winding resistance aux	**12.4 Ohm**
Oil quantity	**298 / 10.08fl.oz**	Max. winding temp.	**125 °C**
Free gas volume comp.	**2,360 cm3 / 79.80fl.oz**	Max. discharge temp.	**130°C / 266°F**
Motor protection	**external**		

Compressor Dimensions

Housing

A Height	**209mm / 8.23in**
B Height	**203mm / 7.99in**
C Length shell	**205mm / 8.07in**
D Length w. cover	**262mm / 10.31in**
E Width	**166mm / 6.54in**

Find 3D Model here



Connectors	Suction X	Discharge Y	Process Z
Diameter [mm]	øi 8.11–8.29 / 0.32–0.33in	øi 6.11–6.29 / 0.24–0.25in	øi 6.11–6.29 / 0.24–0.25in
Material	CU	CU	CU
Horizontal angle ±2°	11°	0°	0°
Vertical angle ±2°	15°	21°	25°
Position l/h/w [mm]	140/72/59 / 5.51/2.83/2.32in	94/98.1/87 / 3.70/3.86/3.43in	-109/93/74 / -4.29/3.66/2.91in
Straight tube l. [mm]	12 / 0.47in	12 / 0.47in	12 / 0.47in

Mounting Accessories



Dimensions in mm [in]

Bolt joint



Snap-on



	one comp.	multi pack
Bolt joint | M6 | ø16mm	118-1917	118-1918
Bolt joint | ø1/4" | ø16mm	118-1946	–
Snap-on | ø7,3 | ø16mm	118-1947	118-1919

Model
NLE15LNDX Configuration 1

Sales code:
105H7500

Configuration

Motor configuration	**CSCR**
Power supply (nominal)	**220-240 V/50 Hz 1~**
Refrigerant	**R290**
Application	**LBP**
Voltage range	**198-254 V**
Starting torque	**HST**
Approvals	**VDE**
Starting device type	**relay**
Run capacitor	**10 µF**
Start capacitor	**80 µF**
LRA (locked rotor amps / 4s/ U(N))	**16.8 A**
RLA (rated load amps / 1s/ U(N))	**2.3 A**
Cut in current (U(N))	**16.8 A**

Ambient/ machine room temperatures minimum /maximum
Ambient temperature range: 10 - 43°C / 50 - 109°F
Machine room temp. compressor: 10 - 48°C / 50 - 118°F

System Cooling
fan 3m/s

Electrical Accessories / Wiring Diagram



View full size

Components
a6 NL starter kit 117U8201
c start capacitor (80µF) 117U5353
e run cap (10µF, 6.3mm,c.length 280mm) 117-7166
b cover terminal board + clamp 117U1038
e1 retaining clamp 117-0314
screw M4x8mm 117-0301
d cord relief 103N1007

Operation Pressure Range





Model
NLE15LNDX Configuration 1

Sales code:
105H7500

Standard Conditions

R290, 220 V/50 Hz, CSCR, fan 3m/s

pe	pc	RGT	Tliq	Cooling capacity			COP	EER	P	I	ṁ	
[°C] [°F]	[°C] [°F]	[°C] [°F]	[°C] [°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]	
-23.3 -10	54.4 129.9	32.2 90	32.2 90	**779**	2658	670	**1.72**	5.88	452	2.16	7.91	**ASHRAE LBP**
-25 -13	55 131	32 89.6	55 131	**585**	1997	503	**1.34**	4.59	436	2.09	7.34	**CECOMAF LBP**
-35 -31	40 104	20 68	40 104	**438**	1494	377	**1.38**	4.69	318	1.61	5.03	**EN12900 LBP**
-23.3 -10	48.8 119.8	4.4 39.9	48.8 119.8	**624**	2128	536	**1.42**	4.84	439	2.10	8.66	**ARI540 LBP**
-23.3 -10	40.6 105.1	32.2 90	32.2 90	**811**	2768	698	**1.95**	6.64	417	2.00	8.24	**AHAM LBP**
-35 -31	45 113	32 89.6	45 113	**422**	1441	363	**1.30**	4.44	325	1.64	4.76	**opt LBP**

Performance Tables

R290, 220 V/50 Hz, CSCR, fan 3m/s

pc= 45/113 | RGT= 32/89.6 | Tliq= 45/113 | °C/°F

pe		Cooling capacity			COP	EER	P	I	ṁ
[°C]	[°F]	[W]	[Btu/h]	[kcal/h]	[W/W]	[Btu/Wh]	[W]	[A]	[kg/h]
-40	-40	**323**	1102	278	**1.14**	3.90	282	1.50	3.63
-35	-31	**422**	1441	363	**1.30**	4.44	325	1.64	4.76
-30	-22	**537**	1832	462	**1.46**	4.97	369	1.80	6.07
-25	-13	**669**	2282	575	**1.62**	5.51	414	1.99	7.58
-20	-4	**820**	2799	705	**1.78**	6.08	460	2.20	9.33
-15	5	**993**	3387	854	**1.96**	6.69	506	2.41	11.34
-10	14	**1188**	4055	1022	**2.15**	7.33	553	2.63	13.65
-5	23	**1410**	4810	1212	**2.35**	8.03	599	2.84	16.28

pc= 55/131 | RGT= 32/89.6 | Tliq= 55/131 | °C/°F

-40	-40	**266**	909	229	**0.92**	3.15	289	1.52	3.31
-35	-31	**360**	1229	310	**1.07**	3.67	335	1.68	4.49
-30	-22	**466**	1589	401	**1.21**	4.14	384	1.87	5.82
-25	-13	**585**	1997	503	**1.34**	4.59	436	2.09	7.34
-20	-4	**721**	2460	620	**1.47**	5.03	489	2.33	9.07
-15	5	**874**	2983	752	**1.60**	5.48	545	2.58	11.06
-10	14	**1048**	3575	901	**1.74**	5.94	602	2.85	13.32
-5	23	**1243**	4241	1069	**1.89**	6.43	660	3.11	15.91



NLE Plus Compressors

Optimized Electrical CSCR System

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

CSCR







NLE Plus Compressors

Optimized Electrical CSCR System

SECOP

Keep electrical equipment clear from oil, chemicals, and water

When operated with a flammable refrigerant, only spark-proof starting equipment is allowed.

Service/Repair – R290, R600a, R170, R1270, R1234yf

(applies to all flammable refrigerants)



Dismantling, recycling, disposal: At the end of a compressor's lifecycle, proceed by separating and storing components according to their environmental impact. Parts that may cause pollution must be clearly identified and handled separately, ensuring appropriate disposal. Refrigerant gas must not be released into the environment and should be recovered by qualified operators. Compressor oil must also be collected separately. The compressor should be disposed of at specialized disposal centers in accordance with the applicable regulations. **Subject to modifications/alterations. www.secop.com**